



COMPONENTI ACERBIS:

- 2** spacer (2 pcs.)
- 3** rubber support (2 pcs.)
- 4** screw 8x10 (2 pcs.)
- 5** petcock dx-sx (2 pcs.)
- 6** gaskets petcock (2 pcs.)
- 7** petcock screw (4 pcs.)
- 8** rubber washer (2 pcs.)
- 9** screws 6x50 (2 pcs.)
- 10** washer 6x24 (2 pcs.)
- 11** tank support (2 pcs.)
- 12** junction Y (1 pcs.)
- 13** fuel tube (1 pcs.)
- 14** cap + gasket (1 pcs.)

OEM ITEMS TO USE:

- 1** gasket seat (1 pcs.)

WE THANK YOU FOR CHOOSING AN:
ORIGINAL ACERBIS PRODUCT!

ASSEMBLY INSTRUCTION

Remove the gasket (1) from seat as shown in figure, take of the original sell locking nuts and tighten the bearings (2) with the rubber mounts (3) and the screws (4) supplied in the mounting kit. Install the laps (5) with the gaskets (6) and the screws (7) With the gaskets (8) mount the Acerbis tank an the frame fix it with the screws (9) the washer (10) and the thicknesses (11). Joint the taps (5) to the carburator with Y-fitting (12) and the rubber breather hose (13) cut in the measures shown in figure. Tighten the gas cap (14) with the rubber breather hose (13).

ACERBIS - REAL PLASTIC FOR REAL LIFE.

WARNING!

Clean tank interior thoroughly before installation. install this fuel tank only in a well ventilated area, as gasoline fumes are extremely dangerous. do not start operate the vehicle if there are any fuel leaks! acerbis recommends that installation be done by licensed mechanic. read all instructions first before beginning installation.

DISCLAIMER:

DISCLAIMER: Due to uncontrolled variables in the manufacturing process of rotationally molded fuel tanks, the fuel tank may vary in size and shape by up 7% of the manufacturer's original listed capacity.