



**We thank you for choosing an  
ORIGINAL ACERBIS PRODUCT!  
ASSEMBLY INSTRUCTIONS**

- Dismount the original fuel tank.
- Apply to the Acerbis fuel tank (1) the petcock (2rev.) on lh side of the fuel tank and (2) on rh side of the fuel tank using the screws (3) and the gaskets provided in the kit. Mount the plates (5) with the original screws (6).
- Position the fuel tank (1) on the motorcycle and fasten it to the frame  
tightening the plates (5).
- Apply the original screws (7) and (8).
- Apply the ACERBIS tap and the rubber tube (9) in the mounting kit.
- For the metallic inserts contained in the fuel tank a maximum clamping torque equal to 7.37 lbf.ft. is guaranteed.
- Quick tap
  - Drill an 8 mm hole in the ACERBIS fuel tank and insert the fuel vent (1) using the gasket (2), the washer (3) and the nut (4) in the kit.
  - Apply the rubber tube to the fuel vent.
- Acerbis tap holder
  - Fasten the ACERBIS tap holder in aluminum (1) utilizing the screws (2) and the gasket (3) in the mounting kit.
  - Apply the ACERBIS tap with the rubber tube provided in the kit.

**WARNING:** Do not ride unless the cap is fully and properly installed. Do not ride if the tank is leaking. Failure to heed this warning can lead to fire and explosion. Gasoline is extremely flammable. Gasoline is highly toxic. Avoid breathing of vapors and avoid skin contact. First Aid: External: Flush with water. Internal: DO NOT induce vomiting. Take activated charcoal in solution. Seek medical help immediately!