



NSFB39 & 41 BEACON FORK MOUNT

- 1- RAISE THE FRONT WHEEL OF THE MOTORCYCLE $\frac{3}{4}$ " OFF OF THE GROUND.
- 2- LOOSEN THE FORK TUBE PINCH BOLTS IN THE TRIPLE TREE AND THE TOP PLUG NUTS IF NECESSARY. SLIDE THE FORK TUBES DOWN THROUGH THE TRIPLE TREE ENOUGH TO GET THE CLAMPS ON THE TUBE. MAKE SURE YOU PLACE THEM ON THE TUBE CORRECTLY.
- 3- SLIDE THE FORK TUBES BACK UP THROUGH THE TRIPLE TREE AND RE-INSTALL AND TIGHTEN NUTS AND PINCH BOLTS.
- 4- SNUG DOWN LARGE SET SCREW IN THE CLAMP, DO NOT TIGHTEN.
- 5- MOUNT THE LIGHT BODY ONTO HOLLOW THREADED STUD AND INSTALL LOCKNUT INSIDE BODY, DO NOT TIGHTEN YET.
- 6- FEED WIRES THROUGH THE HOLLOW STUD AND OUT THE EXIT HOLE IN THE BACK EDGE OF THE CLAMP.
- 7- ROUTE THE WIRES AS DESIRED AND MAKE THE APPROPRIATE ELECTRICAL CONNECTIONS.
- 8- POSITION LIGHTS AS REQUIRED AND TIGHTEN ALL BOLTS, NUTS AND SCREWS (ADJURE RECOMMENDS THE USE OF A DROP OF BLUE THREAD LOCKER).
- 9- INSTALL LIGHT SOURCE INTO BODY AND TEST.
- 10- REPEAT FOR SECOND LIGHT AND CLAMP.