# SAFETY DATA SHEET

## 1. Identification

**Product identifier Bel-Ray Moto Chill Racing Coolant** 

**Product Code** 99410 **SDS** number 6427

Other means of identification Not available. Recommended use **Engine Coolant Recommended restrictions** None known.

# 2. Hazard(s) identification

Not classified. Physical hazards

**Health hazards** Sensitization, skin Category 1

> Reproductive toxicity Category 1

**Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** May cause an allergic skin reaction. May damage fertility or the unborn child.

**Precautionary statement** 

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

> and understood. Avoid breathing mist or vapor. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention.

Specific treatment (see this label). If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

**Mixtures** 

SDS US 1/7 99410 Version #: 3.0

Chemical name	Common name and synonyms	CAS number	%
Propylene Glycol		57-55-6	50 - < 60
Boric Acid (hbo2), Sodium Salt, Tetrahydrate		10555-76-7	<3
Other components below reportab	le levels		40 - < 50

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema

or other skin disorders: Seek medical attention and take along these instructions.

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Do not induce vomiting. Get medical attention if symptoms occur. Never give liquid to

May cause an allergic skin reaction. Dermatitis. Rash.

an unconscious person.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

**General information** 

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

During fire, gases hazardous to health may be formed.

Wear suitable protective equipment. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

#### 6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** 

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

Occupational exposure limits

US. Workplace Environmental Exposure Level (WEEL) Guides

Components Value **Form** Type Propylene Glycol (CAS TWA 10 mg/m3 Aerosol. 57-55-6)

**Biological limit values** No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece. Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

# 9. Physical and chemical properties

Liquid. **Appearance** 

Physical state Liquid. **Form** Liquid. Color Blue. Mild. Odor

**Odor threshold** Not available. Not available. -31 °F (-35 °C) Melting point/freezing point Initial boiling point and 228.2 °F (109 °C)

boiling range

Flash point N/A

**Evaporation rate** Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits **Explosive limit - lower** Not available.

(%)

**Explosive limit - upper** 

(%)

Not available.

0.05 hPa estimated Vapor pressure 1020.00 kg/m<sup>3</sup> Density Not available. Vapor density Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Material name: Bel-Ray Moto Chill Racing Coolant

SDS US 99410 Version #: 3.0

**Partition coefficient** (n-octanol/water)

Not available.

**Auto-ignition temperature** 

None

**Decomposition temperature** 

Not available. Not available.

Other information

**Viscosity** 

Percent volatile 0 % Specific gravity 1.02 VOC 0 %

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Irritants. At thermal decomposition temperatures, carbon monoxide and carbon dioxide.

# 11. Toxicological information

## Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the

physical, chemical and

toxicological characteristics May cause an allergic skin reaction. Dermatitis. Rash.

## Information on toxicological effects

May cause an allergic skin reaction. Causes skin and eye irritation. Causes skin irritation **Acute toxicity** 

Product	Species	Test Results
Bel-Ray Moto Chill Racing Co	polant	
<u>Acute</u>		
Oral		
LD50	Dog	38 g/kg estimated
	Guinea pig	37 g/kg estimated
	Mouse	48 g/kg estimated
	Rabbit	36 g/kg estimated
	Rat	40403 mg/kg estimated
Components	Species	Test Results

Oral

LD50 Rat 2330 mg/kg

Propylene Glycol (CAS 57-55-6)

**Acute** Oral

LD50 Dog 19 g/kg

18.4 g/kg Guinea pig

Material name: Bel-Ray Moto Chill Racing Coolant

4 / 7 99410 Version #: 3.0

Components	Species	Test Results	
	Mouse	23.9 g/kg	
	Rabbit	18 g/kg	
	Rat	30 g/kg	

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Based on available data, the classification criteria are not met. Serious eye damage/eye Based on available data, the classification criteria are not met.

irritation

Respiratory or skin sensitization

Based on available data, the classification criteria are not met. Respiratory sensitization

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity May damage fertility or the unborn child.

Specific target organ toxicity - single exposure Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated

Based on available data, the classification criteria are not met.

**Aspiration hazard** 

exposure

Not an aspiration hazard.

Chronic effects Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood

# 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results	
Bel-Ray Moto Chill Rad	cing Coolant			
Aquatic				
Crustacea	EC50	Daphnia	19995.2012 mg/l, 48 hours estimated	
Fish	LC50	Fish	73964.75 mg/l, 96 hours estimated	
Components		Species	Test Results	
Propylene Glycol (CAS	5 57-55-6)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours	
Fish	LC50	Fathead minnow (Pimephales promelas)	710 mg/l, 96 hours	

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

-0.92 Propylene Glycol

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and

> its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

Local disposal regulations Dispose in accordance with all applicable regulations.

Material name: Bel-Ray Moto Chill Racing Coolant

SDS US 5/7 99410 Version #: 3.0

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

# 14. Transport information

#### DOT

Not regulated as dangerous goods.

#### IATA

Not regulated as dangerous goods.

#### **IMDG**

Not regulated as dangerous goods.

Transport in bulk according to Not established. Annex II of MARPOL 73/78

and the IBC Code

# 15. Regulatory information

**US federal regulations**This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312** No

Hazardous chemical

# SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

Safe Drinking Water Act

Not regulated.

(SDWA)

## **US state regulations**

## US. New Jersey Worker and Community Right-to-Know Act

Boric Acid (hbo2), Sodium Salt, Tetrahydrate (CAS 10555-76-7)

Propvlene Glycol (CAS 57-55-6)

## US. Pennsylvania Worker and Community Right-to-Know Law

Propylene Glycol (CAS 57-55-6)

## **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes

Material name: Bel-Ray Moto Chill Racing Coolant

99410 Version #: 3.0 6 / 7

SDS US

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

# 16. Other information, including date of preparation or last revision

 Issue date
 04-14-2016

 Revision date
 05-14-2016

Version # 3.0

**Disclaimer** Bel-Ray Company, LLC cannot anticipate all conditions under which this information and its product,

or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any

process, unless specified in the text.