

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 06/02/2017 : Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : BLUE MAGIC GLASS CLEANER 19 OZ.

Product code : 910-06

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Glass Cleaner

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Compressed gas H280 STOT SE 1 H370

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





04 GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H280 - Contains gas under pressure; may explode if heated

H370 - Causes damage to organs

Precautionary statements (GHS-US) : P260 - Do not breathe dust, fumes, gas, mist, vapor spray

P264 - Wash affected areas thoroughly after handling P270 - Do not eat, drink or smoke when using this product P307+P311 - If exposed: Call a poison center/doctor P321 - Specific treatment: See section 4.1 on SDS

P405 - Store locked up

P410+P403 - Protect from sunlight. Store in a well-ventilated place

P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with

local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the

classification

 $: \ \, \text{Contains gas under pressure; may explode if heated. None under normal conditions.} \\$

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Water	(CAS No) 7732-18-5	85 - 95	Not classified
Methanol	(CAS No) 67-56-1	1 - 5	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370

02/06/2017 EN (English US) 1/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
Petroleum Gases, Liquefied, Sweetened	(CAS No) 68476-86-8	1 - 5	Flam. Gas 1, H220 Compressed gas, H280
Ethanol	(CAS No) 64-17-5	0.6545 - 0.693	Flam. Liq. 2, H225
2-Butoxyethanol	(CAS No) 111-76-2	<1	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
2-Aminoethanol	(CAS No) 141-43-5	<= 0.0493	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314
Additive Package	(CAS No) Proprietary	< 1	Not classified
Double-Encapped PAG 100	(CAS No) Proprietary	< 1	Acute Tox. 4 (Oral), H302
2-Propanol	(CAS No) 67-63-0	0 - 0.0385	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Proprietary Inhibitor Package	(CAS No) Proprietary	<= 0.0174	Not classified
Methyl Isobutyl Ketone	(CAS No) 108-10-1	0 - 0.0077	Flam. Liq. 2, H225 Acute Tox. 3 (Inhalation:gas), H331 Eye Irrit. 2A, H319 STOT SE 3, H335

The exact percentage is a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a POISON CENTER or doctor/physician.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed

by warm water rinse.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with

water for several minutes. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes damage to organs.

Symptoms/injuries after skin contact : May cause slight irritation . May cause moderate irritation. Itching. Red skin. Skin

rash/inflammation.

Symptoms/injuries after eye contact : May cause slight irritation. May cause slight eye irritation . Inflammation/damage of the eye

tissue. Irritation of the eye tissue. Redness of the eye tissue.

Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : NFPA Aerosol Level 1.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

02/06/2017 EN (English US) 2/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Plug the leak, cut off the supply. Contain released substance, pump into

suitable containers.

Methods for cleaning up : Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor. Do not breathe dust,fumes,gas,mist,vapor spray.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash

: Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Separate working clothes from town clothes. Launder separately. Remove contaminated clothes. Always wash hands after handling the product. Wash affected areas thoroughly after

handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with

applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container

closed when not in use.

Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.
Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Detroloum Cooks Lim	refied Sweetened (69.476 96 9)	
	uefied, Sweetened (68476-86-8)	
USA ACGIH	ACGIH TWA (ppm)	1000 ppm Listed under Aliphatic hydrocarbon gases alkane C1-C4
USA OSHA	OSHA PEL (TWA) (mg/m³)	1800 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
2-Butoxyethanol (111-	76-2)	
USA ACGIH	ACGIH TWA (mg/m³)	97 mg/m³
USA ACGIH	ACGIH TWA (ppm)	20 ppm (2-Butoxyethanol (EGBE); USA; Time- weighted average exposure limit 8 h; TLV - Adopted Value)
USA OSHA	OSHA PEL (TWA) (mg/m³)	240 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
2-Aminoethanol (141-4	13-5)	
USA ACGIH	ACGIH TWA (ppm)	3 ppm (Ethanolamine; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (ppm)	6 ppm (Ethanolamine; USA; Short time value; TLV - Adopted Value)
Methanol (67-56-1)		
USA ACGIH	ACGIH TWA (mg/m³)	262 mg/m³
USA ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (mg/m³)	328 mg/m³

02/06/2017 EN (English US) 3/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)		
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Methyl Isobutyl Ketone (108-10-1)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm (Methyl isobutyl ketone; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)

75 ppm (Methyl isobutyl ketone; USA; Short time

value; TLV - Adopted Value)

8.2. Exposure controls

USA ACGIH

Appropriate engineering controls : Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.





Materials for protective clothing : GIVE EXCELLENT RESISTANCE:

ACGIH STEL (ppm)

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended.

Environmental exposure controls : Avoid release to the environment.

Consumer exposure controls : Avoid contact during pregnancy/while nursing.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
Appearance : Liquid.

Color : Colourless to light yellow.
Odor : Mild . Alcohol odour.
Odor threshold : No data available

pH : 9

Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available
Freezing point : No data available

Boiling point : -31.1 °C (Lowest Component-Propellant)
Flash point : -96.23 °C (Lowest Component-Propellant)

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available

Relative density : 0.98

Solubility : Soluble in water. Log Pow : No data available : No data available Log Kow Viscosity, kinematic : No data available Viscosity, dynamic : No data available : No data available Explosive properties No data available Oxidizing properties **Explosion limits** : No data available

9.2. Other information

VOC content : < 10 %

02/06/2017 EN (English US) 4/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Specific target organ toxicity - repeated

Potential Adverse human health effects and

exposure

symptoms

Aspiration hazard

Acute toxicity : Not classified

Acute toxicity	: Not classified
2-Butoxyethanol (111-76-2)	
LD50 oral rat	1300 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg (435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value,435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	450-486,Rat; Weight of evidence
2-Aminoethanol (141-43-5)	
LD50 oral rat	1720 mg/kg (Rat)
LD50 dermal rabbit	1018 mg/kg (Rabbit)
Methanol (67-56-1)	
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air
Methyl Isobutyl Ketone (108-10-1)	
LD50 oral rat	2080 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rat	>= 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	8.2- 16.4,Rat; Experimental value
LC50 inhalation rat (ppm)	2000 ppm/4h (Rat; Experimental value,Rat; Experimental value)
Double-Encapped PAG 100 (Proprietary)	
LD50 oral rat	500 mg/kg
Skin corrosion/irritation	: Not classified
	pH: 9
Serious eye damage/irritation	: Not classified
	pH: 9
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
2-Butoxyethanol (111-76-2)	
IARC group	3
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Causes damage to organs.
apasina tangat argan taman, anigia apadara	. Caused Lamage to organic.

02/06/2017 EN (English US) 5/12

: Based on available data, the classification criteria are not met.

: Not classified

: Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after skin contact

: May cause slight irritation . May cause moderate irritation. Itching. Red skin. Skin rash/inflammation.

Symptoms/injuries after eye contact

: May cause slight irritation. May cause slight eye irritation . Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue.

Symptoms/injuries after ingestion

: May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

2-Aminoethanol (141-43-5)	
LC50 fish 1	150 mg/l (LC50; 96 h; Salmo gairdneri)
EC50 Daphnia 1	140 mg/l (EC50; 24 h)
Threshold limit algae 2	35 mg/l (EC50; 72 h)
Methanol (67-56-1)	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)

12.2. Persistence and degradability

Proprietary Inhibitor Package (Proprietary)

BLUE MAGIC GLASS CLEANER 19 OZ.	
Persistence and degradability	Not established.

Petroleum Gases, Liquefied, Sweetened (68476-86-8)		
Persistence and degradability	Not established.	
2-Butoxyethanol (111-76-2)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.	
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance	
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance	
ThOD	2.305 g O ₂ /g substance	
BOD (% of ThOD)	0.31	
2-Aminoethanol (141-43-5)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.	

2-Aminoethanol (141-43-5)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.
Biochemical oxygen demand (BOD)	0.8 g O ₂ /g substance
Chemical oxygen demand (COD)	1.34 g O ₂ /g substance
ThOD	2.49 g O ₂ /g substance
BOD (% of ThOD)	0.32

Persistence and degradability	Not established.	
Methanol (67-56-1)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.	
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance	
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance	
ThOD	1.5 g O ₂ /g substance	
BOD (% of ThOD)	0.8 (Literature study)	
Water (7732-18-5)		

11410. (1162 16 6)	
Persistence and degradability	Not established.

Methyl Isobutyl Ketone (108-10-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Low potential for adsorption in soil. Photolysis in the air. Not established.
Biochemical oxygen demand (BOD)	2.06 g O ₂ /g substance
Chemical oxygen demand (COD)	2.16 g O ₂ /g substance
ThOD	2.72 g O ₂ /g substance
BOD (% of ThOD)	0.76
Addition Dealers (Decembers)	

BOD (% of INOD)	0.76	
Additive Package (Proprietary)		
Persistence and degradability	Not established.	
Double-Encapped PAG 100 (Proprietary)		
Persistence and degradability	Not established.	
BOD (% of ThOD)	< 5 % ThOD	

02/06/2017 EN (English US) 6/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BLUE MAGIC GLASS CLEANER 19 OZ. Bioaccumulative potential Not established. Petroleum Gases, Liquefied, Sweetened (68476-86-8) Bioaccumulative potential Not established. 2-Butoxyethanol (111-76-2) Log Pow 0.81 (Experimental value; BASF test; 25 °C) Bioaccumulative potential Low potential for bioaccumulation (Log Kow < 4). 2-Aminoethanol (141-43-5) Log Pow 1-1.91 Bioaccumulative potential Bioaccumulation: not applicable. Proprietary Inhibitor Package (Proprietary) Bioaccumulative potential Not established. Methanol (67-56-1) BCF fish 1 < 10 (BCF; 72 h; Leuciscus idus) Log Pow -0.77 (Experimental value; OHer) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Water (7732-18-5) Bioaccumulative potential Not established. Methyl Isobutyl Ketone (108-10-1) BCF fish 1 2 - 5 (BCF) Log Pow 1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method) Bioaccumulative potential Low potential robioaccumulation (BCF < 500). Not established. Additive Package (Proprietary) Bioaccumulative potential Not established. Additive Package (Proprietary) Bioaccumulative potential Not established. Double-Encapped PAG 100 (Proprietary) Bioaccumulative potential Not established. 2-4 Mobility in soil 2-5 Minoethanol (111-76-2) Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension 0.023 N/m (20 °C) Log Koc. PCKOCWIN v1.66; 1; Calculated value	12.3. Bioaccumulative potential			
Petroleum Gases, Liquefied, Sweetened (68476-86-8) Bioaccumulative potential Not established. 2-Butoxyethanol (111-76-2) Log Pow 0.81 (Experimental value; BASF test; 25 °C) Bioaccumulative potential Low potential for bioaccumulation (Log Kow < 4). 2-Aminoethanol (141-43-5) Log Pow 1-1.91 Bioaccumulative potential Bioaccumulative potential Bioaccumulative potential Bioaccumulative potential Not established. Proprietary Inhibitor Package (Proprietary) Bioaccumulative potential Not established. Methanol (67-56-1) BCF fish 1 < 10 (BCF; 72 h: Leuciscus idus) Log Pow 0-0.77 (Experimental value; Other) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Water (7732-18-5) Bioaccumulative potential Not established. Methyl Isobutyl Ketone (108-10-1) BCF fish 1 2 - 5 (BCF) Log Pow 1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Not established. Additive Package (Proprietary) Bioaccumulative potential Not established. Double-Encapped PAG 100 (Proprietary) Bioaccumulative potential Not established. Double-Encapped PAG 100 (Proprietary) Bioaccumulative potential Not established. Proprietary Not established. Double-Encapped PAG 100 (Proprietary) Bioaccumulative potential Not established.	BLUE MAGIC GLASS CLEANER 19 OZ.			
Bioaccumulative potential Not established.	Bioaccumulative potential	Not established.		
2-Butoxyethanol (111-76-2) Log Pow	Petroleum Gases, Liquefied, Sweetened (68476-86-8)			
Log Pow				
Bioaccumulative potential Low potential for bioaccumulation (Log Kow < 4). 2-Aminoethanol (141-43-5) Log Pow -1.91 Bioaccumulative potential Bioaccumulation: not applicable. Proprietary Inhibitor Package (Proprietary) Bioaccumulative potential Not established. Methanol (67-56-1) BCF fish 1 < 10 (BCF; 72 h; Leuciscus idus) Log Pow -0.77 (Experimental value; Other) Bioaccumulative potential Not established. Methyl Isobutyl Ketone (108-10-1) BCF fish 1 2 - 5 (BCF) Log Pow 1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Not established. Additive Package (Proprietary) Bioaccumulative potential Not established. Double-Encapped PAG 100 (Proprietary) Bioaccumulative potential Not established. 2-Butoxyethanol (111-76-2) Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (67-56-1) Surface tension 0.023 N/m (20 °C)	2-Butoxyethanol (111-76-2)			
2-Aminoethanol (141-43-5) Log Pow	Log Pow	0.81 (Experimental value; BASF test; 25 °C)		
Log Pow -1.91 Bioaccumulative potential Bioaccumulation: not applicable. Proprietary Inhibitor Package (Proprietary) Bioaccumulative potential Not established. Methanol (67-56-1) BCF fish 1 < 10 (BCF; 72 h; Leuciscus idus) Log Pow -0.77 (Experimental value; Other) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Water (7732-18-5) Bioaccumulative potential Not established. Methyl Isobutyl Ketone (108-10-1) BCF fish 1	Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
Bioaccumulative potential Bioaccumulation: not applicable. Proprietary Inhibitor Package (Proprietary) Bioaccumulative potential Not established. Methanol (67-56-1) BCF fish 1 < 10 (BCF; 72 h; Leuciscus idus) Log Pow -0.77 (Experimental value; Other) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Water (7732-18-5) Bioaccumulative potential Not established. Methyl Isobutyl Ketone (108-10-1) BCF fish 1	2-Aminoethanol (141-43-5)			
Proprietary Inhibitor Package (Proprietary) Bioaccumulative potential Not established. Methanol (67-56-1) BCF fish 1 < 10 (BCF; 72 h; Leuciscus idus) Log Pow -0.77 (Experimental value; Other) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Water (7732-18-5) Bioaccumulative potential Not established. Methyl Isobutyl Ketone (108-10-1) BCF fish 1	Log Pow	-1.91		
Bioaccumulative potential Not established. Methanol (67-56-1) BCF fish 1	Bioaccumulative potential	Bioaccumulation: not applicable.		
Methanol (67-56-1) BCF fish 1	Proprietary Inhibitor Package (Proprietary)			
BCF fish 1 < 10 (BCF; 72 h; Leuciscus idus) Log Pow	Bioaccumulative potential	Not established.		
BCF fish 1 < 10 (BCF; 72 h; Leuciscus idus) Log Pow	Methanol (67-56-1)			
Log Pow -0.77 (Experimental value; Other) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Water (7732-18-5) Bioaccumulative potential Not established. Methyl Isobutyl Ketone (108-10-1) BCF fish 1 2 - 5 (BCF) Log Pow 1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Not established. Additive Package (Proprietary) Bioaccumulative potential Not established. Double-Encapped PAG 100 (Proprietary) Bioaccumulative potential Not established. 12.4. Mobility in soil 2-Butoxyethanol (111-76-2) Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension 0.023 N/m (20 °C)	,	< 10 (BCF; 72 h; Leuciscus idus)		
Water (7732-18-5) Bioaccumulative potential Not established. Methyl Isobutyl Ketone (108-10-1) BCF fish 1 2 - 5 (BCF) Log Pow 1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Not established. Additive Package (Proprietary) Bioaccumulative potential Not established. Double-Encapped PAG 100 (Proprietary) Bioaccumulative potential Not established. 12.4. Mobility in soil 2-Butoxyethanol (111-76-2) Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension 0.05 N/m Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)	Log Pow	-0.77 (Experimental value; Other)		
Bioaccumulative potential Not established. Methyl Isobutyl Ketone (108-10-1) BCF fish 1 2 - 5 (BCF) Log Pow 1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Not established. Additive Package (Proprietary) Bioaccumulative potential Not established. Double-Encapped PAG 100 (Proprietary) Bioaccumulative potential Not established. 12.4. Mobility in soil 2-Butoxyethanol (111-76-2) Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension 0.05 N/m Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)	Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).		
Methyl Isobutyl Ketone (108-10-1) BCF fish 1 2 - 5 (BCF) Log Pow 1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Not established.	Water (7732-18-5)			
BCF fish 1 Log Pow 1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Not established. Additive Package (Proprietary) Bioaccumulative potential Not established. Double-Encapped PAG 100 (Proprietary) Bioaccumulative potential Not established. 12.4. Mobility in soil 2-Butoxyethanol (111-76-2) Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension 0.05 N/m Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)	Bioaccumulative potential	Not established.		
Log Pow 1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Not established. Additive Package (Proprietary) Bioaccumulative potential Not established. Double-Encapped PAG 100 (Proprietary) Bioaccumulative potential Not established. 12.4. Mobility in soil 2-Butoxyethanol (111-76-2) Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension 0.05 N/m Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)	Methyl Isobutyl Ketone (108-10-1)			
Log Pow 1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method) Bioaccumulative potential Low potential for bioaccumulation (BCF < 500). Not established. Additive Package (Proprietary) Bioaccumulative potential Not established. Double-Encapped PAG 100 (Proprietary) Bioaccumulative potential Not established. 12.4. Mobility in soil 2-Butoxyethanol (111-76-2) Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension 0.05 N/m Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)	BCF fish 1	2 - 5 (BCF)		
Additive Package (Proprietary) Bioaccumulative potential Not established. Double-Encapped PAG 100 (Proprietary) Bioaccumulative potential Not established. 12.4. Mobility in soil 2-Butoxyethanol (111-76-2) Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension 0.05 N/m Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)	Log Pow	1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method)		
Bioaccumulative potential Not established. Double-Encapped PAG 100 (Proprietary) Bioaccumulative potential Not established. 12.4. Mobility in soil 2-Butoxyethanol (111-76-2) Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension 0.05 N/m Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)	Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500). Not established.		
Double-Encapped PAG 100 (Proprietary) Bioaccumulative potential Not established. 12.4. Mobility in soil 2-Butoxyethanol (111-76-2) Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension 0.05 N/m Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)	Additive Package (Proprietary)			
Bioaccumulative potential Not established. 12.4. Mobility in soil 2-Butoxyethanol (111-76-2) Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension 0.05 N/m Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)	Bioaccumulative potential	Not established.		
12.4. Mobility in soil 2-Butoxyethanol (111-76-2) Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension 0.05 N/m Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)				
2-Butoxyethanol (111-76-2) Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension 0.05 N/m Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)	Bioaccumulative potential	Not established.		
Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension Surface tension 0.05 N/m Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)	12.4. Mobility in soil			
Surface tension 0.027 N/m (25 °C) 2-Aminoethanol (141-43-5) Surface tension Surface tension 0.05 N/m Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)	2-Butoxyethanol (111-76-2)			
2-Aminoethanol (141-43-5) Surface tension 0.05 N/m Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)		0.027 N/m (25 °C)		
Surface tension 0.05 N/m Methanol (67-56-1) 0.023 N/m (20 °C)				
Methanol (67-56-1) Surface tension 0.023 N/m (20 °C)	` ,	0.05 N/m		
Surface tension 0.023 N/m (20 °C)				
	,	0.023 N/m (20 °C)		
Methyl Isobutyl Ketone (108-10-1)				
Surface tension 0.024 N/m (20 °C)	,	0.024 N/m (20 °C)		
Log Koc Koc, 101.85; Weight of evidence; Calculated value; log Koc; 2.008; Weight of evidence; Calculated value		Koc,101.85; Weight of evidence; Calculated value; log Koc; 2.008; Weight of evidence;		

Other adverse effects 12.5.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

Waste treatment methods

: Container under pressure. Do not drill or burn even after use. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste Product/Packaging disposal recommendations

disposal facility, in accordance with local, regional, national, international regulations.

: Avoid release to the environment. Ecology - waste materials

EN (English US) 02/06/2017 7/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1950, Aerosols, 2.2, Limited Quantity ICAO/IATA (air): UN1950, Aerosols, 2.2, Limited Quantity IMO/IMDG (water): UN1950, Aerosols, 2.2, Limited Quantity

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols

Non-flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

BLUE MAGIC GLASS CLEANER 19 OZ.		
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Sudden release of pressure hazard	
D. (m. 1. m. 1. m. 1. m. 1. m. 1. m. 1. (20.470.00.0)		

Petroleum Gases, Liquefied, Sweetened (68476-86-8)

, ,	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
	Fire hazard
	Sudden release of pressure hazard

2-Butoxyethanol (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard	

2-Aminoethanol (141-43-5)

SARA Section 311/312 Hazard Classes Immediate (acute) health hazard

Fire hazard

Methanol (67-56-1)

Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on the United States SARA Section 302 Listed on the United States SARA Section 355

02/06/2017 EN (English US) 8/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard
Double-Encapped PAG 100 (Proprietary)	

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

BLUE MAGIC GLASS CLEANER 19 OZ.			
WHMIS Classification	HMIS Classification Class A - Compressed Gas		
2-Butoxyethanol (111-76-2)			
Listed on the Canadian DSL (Domestic Substances List)			
Methanol (67-56-1)			
Listed on the Canadian DSL (Domestic Substances List)			
WHMIS Classification Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects			
Double-Encapped PAG 100 (Proprieta	arv)		

EU-Regulations

2-Butoxyethanol (111-76-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Double-Encapped PAG 100 (Proprietary)

Listed on the Canadian DSL (Domestic Substances List)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.1; R45 Muta.Cat.2; R46 F+; R12 Xn; R20/21/22 Xn; R68/20/21/22

Full text of R-phrases: see section 16

National regulations

2-Butoxyethanol (111-76-2)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Korean ECL (Existing Chemicals List)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Methanol (67-56-1)

Listed on the Canadian IDL (Ingredient Disclosure List)

Double-Encapped PAG 100 (Proprietary)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

15.3. US State regulations

BLUE MAGIC GLASS CLEANER 19 OZ.	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No

02/06/2017 EN (English US) 9/12

New Jersey Right-to-Know Minnesota Right-to-Know

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	ANER 19 OZ.			
State or local regulations		U.S California - Proposition	65	
Petroleum Gases, Liquefic	ed, Sweetened (68476-86-8)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk leve (NSRL)
No	No	No	No	
2-Butoxyethanol (111-76-2	2)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk leve (NSRL)
No	No	No	No	
2-Aminoethanol (141-43-5)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk leve (NSRL)
No	No	No	No	
Proprietary Inhibitor Pack	age (Proprietary)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk leve (NSRL)
No	No	No	No	
Methanol (67-56-1)			- I	
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk leve (NSRL)
No	Yes	No	No	
Water (7732-18-5)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk leve (NSRL)
No	No	No	No	
Methyl Isobutyl Ketone (10	08-10-1)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk leve (NSRL)
Yes	No	No	No	
Additive Package (Proprie	tary)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk leve (NSRL)
No	No	No	No	
Double-Encapped PAG 10	0 (Proprietary)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk leve (NSRL)
No	No	No	No	
No	No Red, Sweetened (68476-86-8)	No	No	

02/06/2017 EN (English US) 10/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Petroleum Gases, Liquefied, Sweetened (68476-86-8)

Rhode Island Right to Know

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

2-Butoxyethanol (111-76-2)

State or local regulations

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - New Jersey - Right to Know Hazardous Substance List

Methanol (67-56-1)

State or local regulations

U.S. - California - Proposition 65 New Jersey Right-to-Know

Florida Right to Know

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) List

Methyl Isobutyl Ketone (108-10-1)

State or local regulations

U.S. - California - Proposition 65

SECTION 16: Other information

Indication of changes : Revision - See : *.

Other information : None.

Full text of H-phrases:

H220	Extremely flammable gas
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H370	Causes damage to organs


NFPA health hazard : 1 - Exposure could cause irritation but only minor residual

injury even if no treatment is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 1 Slight Hazard Physical : 1 Slight Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC