OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/05/2014

### 1 Identification

· Product identifier: 13103, 13105, 13126, 13127, 13128, 13310, 13322, 13451, 14137, 14139, 14140, 14152,

14153, 14154, 14159, 14401, 14404, 15169, 15262

· Trade name: Rubber Patch

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.



**GHS09 Environment** 

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms







GHS07 GHS08 GHS09

- · Signal word Danger
- · Hazard-determining components of labeling:

1,3-butadiene buta-1,3-diene

benzothiazole-2-thiol

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/05/2014

#### Trade name: Rubber Patch

(Contd. of page 1)

Carbon black

calcium carbonate

#### · Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

May cause respiratory irritation.

Toxic to aquatic life with long lasting effects.

#### · Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If on skin: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 1 Reactivity = 0

### · HMIS-ratings (scale 0 - 4)



## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture: consisting of the following components.

(Contd. on page 3)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/05/2014

Trade name: Rubber Patch

(Contd. of page 2)

· Dangerous	Components:	
1333-86-4	Carbon black	14.8-15.5%
	🕸 Carc. 2, H351; 🕦 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
471-34-1	calcium carbonate	3.8-6.2%
	♦ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	
1314-13-2	zinc oxide	3.8-4.2%
	♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
9006-04-6	Natural rubber latex	23-24%
106-99-0	1,3-butadiene buta-1,3-diene	23-24%
	♦ Flam. Gas 1, H220; ♦ Muta. 1B, H340; Carc. 1A, H350; Press. Gas, H280	-
1332-58-7	Argil	7.3-7.7%
10279-57-9	White Carbon Black	9.7-10.5%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2B, H320	
7704-34-9	sulfur	1.8-2.2%
	♦ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320; Combustible Dust	

### 4 First-aid measures

- · Description of first aid measures
- After inhalation: Not a normal route of entry.
- · After skin contact: Wash with soap and water.
- · After eve contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Not anticipated under normal use.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# 5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Use the appropriate tools to collect the material and dispose of it in an approved waste diposal container. Dispose contaminated material as waste according to section 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/05/2014

Trade name: Rubber Patch

(Contd. of page 3)

### 7 Handling and storage

- · Precautions for safe handling No special precautions are necessary if used correctly.
- Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with occupational exposure limits:

#### 1333-86-4 Carbon black

PEL | Long-term value: 3.5 mg/m³

REL Long-term value: 3.5\* mg/m³

\*0.1 in presence of PAHs; See Pocket Guide Apps. A+C

TLV | Long-term value: 3\* mg/m³

\*inhalable fraction

#### 471-34-1 calcium carbonate

PEL Long-term value: 15\* 5\*\* mg/m³

\*total dust \*\*respirable fraction

REL Long-term value: 10\* 5\*\* mg/m<sup>3</sup>

\*total dust \*\*respirable fraction

TLV | TLV withdrawn

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · Breathing equipment: Not required.
- · Protection of hands: Not required.
- · Eye protection: Not required.

### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:
Color:
Black
Odor:
Codor threshold:
Rubber Patch
Black
Like Rubber
Not determined.

PH-value:
Not determined.

· Change in condition

Melting point/Melting range: Not determined. Boiling point/Boiling range: Not determined.

(Contd. on page 5)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/05/2014

Trade name: Rubber Patch

(Contd. of page 4)

Flash point: Not applicable.Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

**Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

Danger of explosion:
 Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined. Not determined.

• Vapor pressure: Not determined.

· Density:

Relative densityNot determined.Vapour densityNot determined.Evaporation rateNot determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

**Other information** No further relevant information available.

### \* 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- Thermal decomposition / conditions to be avoided:

Carbon dioxide and carbon monoxide may form when heated to decomposition

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

1333-86-4 Carbon black

Oral LD50 10000 mg/kg (rat)

1314-13-2 zinc oxide

Oral LD50 > 5000 mg/kg (rat)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye:
  Irritating effect.

(Contd. on page 6)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/05/2014

#### Trade name: Rubber Patch

(Contd. of page 5)

Causes serious eye irritation.

#### · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic.

#### · Carcinogenic categories

### IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

106-99-0	1,3-butadiene buta-1,3-diene	1
1333-86-4	Carbon black	2B
· NTP (Natio	onal Toxicology Program)	
106-99-0 1	,3-butadiene buta-1,3-diene	K
· OSHA-Ca	(Occupational Safety & Health Administration)	
None of the	e ingredients are listed.	

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

#### 14 Transport information

- · UN-Number
- · DOT, ADR, ADN, IMDG, IATA

Non-Regulated Material

(Contd. on page 7)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/05/2014

Trade name: Rubber Patch

(Contd. of page 6)

· UN proper shipping name

DOT, ADR, ADN, IMDG, IATA Non-Regulated Material

· Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Non-Regulated Material

· Packing group

· DOT, ADR, IMDG, IATA Non-Regulated Material

· Environmental hazards:

· Marine pollutant:

· Special precautions for user Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation":

### 5 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture

Sara		
· Section 355 (extreme	ly hazardous substances	):

None of the ingredients are listed.

#### · Section 313 (Specific toxic chemical listings):

106-99-0 1,3-butadiene buta-1,3-diene

1314-13-2 zinc oxide

#### · TSCA (Toxic Substances Control Act):

106-99-0 1,3-butadiene buta-1,3-diene

1333-86-4 Carbon black

471-34-1 calcium carbonate

1332-58-7 Argil

1314-13-2 zinc oxide

7704-34-9 sulfur

· Proposition 65

### · Chemicals known to cause cancer:

106-99-0 1.3-butadiene buta-1.3-diene

1333-86-4 | Carbon black

#### · Chemicals known to cause reproductive toxicity for females:

106-99-0 1,3-butadiene buta-1,3-diene

### · Chemicals known to cause reproductive toxicity for males:

106-99-0 1,3-butadiene buta-1,3-diene

#### · Chemicals known to cause developmental toxicity:

106-99-0 1,3-butadiene buta-1,3-diene

(Contd. on page 8)

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/05/2014

Trade name: Rubber Patch

(Contd. of page 7)

### · Carcinogenic categories

· EPA (Envi	ronmental Protection Agency)	
106-99-0	1,3-butadiene buta-1,3-diene	СаН
1314-13-2	zinc oxide	D, I, II
· TLV (Thre	shold Limit Value established by ACGIH)	
106-99-0	1,3-butadiene buta-1,3-diene	A2
1333-86-4	Carbon black	A4
1332-58-7	Argil	2 mg/m3
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	
106-99-0	1,3-butadiene buta-1,3-diene	
1333-86-4	Carbon black	

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

#### · Hazard pictograms







GHS07 GHS08 GHS09

### · Signal word Danger

#### Hazard-determining components of labeling:

1,3-butadiene buta-1,3-diene

benzothiazole-2-thiol

Carbon black

calcium carbonate

#### · Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

May cause respiratory irritation.

Toxic to aquatic life with long lasting effects.

### Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/05/2014

Trade name: Rubber Patch

(Contd. of page 8)

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If on skin: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

### · National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

1333-86-4	Carbon black	14.8-15.5%
1000 00 1	♦ Carc. 2, H351; ♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	- 11.0 10.070
471-34-1	calcium carbonate	3.8-6.2%
	♦ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	
1314-13-2	zinc oxide	3.8-4.2%
	♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
9006-04-6	Natural rubber latex	23-24%
106-99-0	1,3-butadiene buta-1,3-diene	23-24%
	♦ Flam. Gas 1, H220; ♦ Muta. 1B, H340; Carc. 1A, H350; Press. Gas, H280	_
1332-58-7	Argil	7.3-7.7%
10279-57-9	White Carbon Black	9.7-10.5%
	♦ Skin Irrit. 2, H315; Eye Irrit. 2B, H320	
7704-34-9	sulfur	1.8-2.2%
	♦ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320; Combustible Dust	_

#### · Information about limitation of use:

#### 16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

<sup>·</sup> Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Reviewed on 11/05/2014

# Trade name: Rubber Patch

(Contd. of page 9)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1 Press. Gas: Gases under pressure: Compressed gas Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 Muta. 1B: Germ cell mutagenicity, Hazard Category 1B Carc. 1A: Carcinogenicity, Hazard Category 1A Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2