


## 2.) 3 - POINT MOUNTING




- 1.) Take one of the two enclosed 43" webbing straps and the "dogbone" foam retainer, and run one end of the strap through one end of the dogbone and add a male buckle end to the strap. (fig. 1)
- 2.) Place dogbone across the front of the tank; taking the loose end, feed it around the down tubes directly below the steering head being careful not to interfere with any wires, cables or the steering of the motorcycle. (figs. 2 & 3)
- 3.) Thread loose end of strap through other end of dogbone and attach a male buckle to this end. Connect both buckle ends to ones on tankbag. (figs. 3 & 4)




- 4.) Remove (or open) seat and thread an end of the remaining strap under the frame tubes. (be careful not to pinch any wires or tubes) Re-thread strap through buckle (see fig. 7, below) and connect rear buckle.

fig. 5



## 3.) 4 - POINT MOUNTING



QuickClips™ straps shown in place here




Male Buckle End pass strap through path made by arrow

Note: this very quick on-and-off mounting style works best using QuickClips™ (on those motorcycles whose tanks will accommodate QuickClips™)

- 1.) Position tank bag.
- 2.) Attach straps on one side of the tank (either QuickClips™ or Loop Pull straps) and adjust to slightly tighter than centered.
- 3.) Attach the straps from the other side and cinch tightly to a secure fit— that's it!


## QUICKCLIP™ STRAPS




QuickClips™ are fast-mount straps that fit on the lower side seam of a motorcycle tank. They may not fit some motorcycles with tightly fit body sections against the tank's lower area. To mount QuickClips™:

- 1.) Attach QuickClips™ straps to tank bag and mount bag on the tank in the proper position.
- 2.) On ONE SIDE, position QuickClips™ on the tank's lower edge, fitting clip to the seam. (see fig. 8 cross section)
- 3.) Adjust the straps and then attach the second side's straps in the same manner. (fig. 9)


(To release straps, lift up on the head of the buckle at a 45° angle)



## LOOP PULL STRAPS



Loop Pull straps (fig. 10) are used to mount a tank bag in any position, front, side or rear on any frame member. and in particular where bodywork precludes the use of QuickClips™. To mount these straps:



- 1.) Simply loop the strap around any secure frame member (as close as possible to the tank) and put the free end through the loop. (fig. 11)
- 2.) Mount the male buckle end to the strap (fig. 7), adjust the length and snap the buckle end to the corresponding female end on the tank bag.