

Items Supplied >

1 - Sissy Bar Rack

Application(s) >

HONDA VLX600 98-07, ACE 750 98-03, SPIRIT 750 01-07, AERO 750 04-09, ACE1100/TOURER 95-99, VT1100 ALL (EXCEPT AERO), VTX1300C/R/S, VTX1800C/R/S/F 02-09 KAWASAKI VULCAN 800A 95-05 YAMAHA ROAD STAR 1600/1700 99-09

Instruction Manual >

02-3500

- 1. Working on the right hand side of the motorcycle, remove the two bolts, which secure the sissy bar to the support bracket. Set the bolts aside for reassembly.
- 2. Carefully slide the sissy bar rack between the support bracket and sissy bar, aligning the holes.
- 3. Install the bolts removed in Step 1 and finger tighten.
- 4. Repeat steps 1 through 3 on the left hand side of the motorcycle.
- 5. Tighten bolts to 12 ft. lbs.

* Cobra sissy bar racks are designed to fit with Cobra sissy bars only *

* Cobra recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.

04/01

Anything's Possible.

Looking for dependable motorcycle luggage rack & support? Rely on Cobra USA for quality and long-lasting products.