

# COBRA®

## Items Supplied >

- 1 – FORMED LUGGAGE RACK
- 4 – M8 X 20mm BUTTONHEAD ALLEN BOLTS

## Application(s) >

COBRA SISSY BAR APPLICATIONS

## Instruction Manual >

02-3602B

1. Remove the buttonhead allen bolts securing the sissy bar to the side mounting brackets, these bolts will not be used again.
2. Install the luggage rack between the side mounting brackets and sissy bar, refer to Figure 1.
3. Install supplied M8 x 20 mm Buttonhead allen bolts and torque to 20 ft-lbs or 28 N-m.

**NOTE:** THIS LUGGAGE RACK IS ONLY INTENDED TO FUNCTION WITH COBRA MANUFACTURED SISSY BAR APPLICATIONS.

SISSY BAR

SISSY  
BAR SIDE  
BRACKET

LUGGAGE  
RACK



FIGURE 1

To clean your black accessory use a liquid based soap detergent, such as dishwashing soap applied with a soft cloth and rinse with clean water. Note: Avoid abrasive cleaning methods such as granular or dry cleansers, simple green, Scotch-Brite or steel wool pads. Abrasives may breach the coating and shorten life.

\* Cobra recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.

DOCUMENT NO. 0019REV. B  
03/10

**Anything's Possible®**

Looking for dependable motorcycle luggage rack & support? Rely on Cobra USA for quality and long-lasting products.