COBRA.

1 -	ms Supplied > LEFT DETACHABLE MTG BRACKET RIGHT DETACHABLE MTG BRACKET		Application(s) > HARLEY: DRESSER	14-20
Ins	struction Manual >		602-2101	Page 1 of 2
Pl€ 1. 2. 3.	ease see the catalog for more details. Remove the saddle bags carefully. Starting on the right side, remove the (2) screws holding the slot cover in place and remove the slot cover by lifting it up out of the slot. Save the two screws. See FIGURE 1 . Insert the right side bracket into the slot of the rear frame section. Apply blue loctite to the (2) stock screws and			
4.	insert them through the holes in the rear frame section, through the mounting bracket, and into the threads of the rear frame section. Snug the screws but DO NOT TIGHTEN at this time. See FIGURE 2 . Do the same for the left side. Snug the screws but DO NOT TIGHTEN at this time.			
5.	Before fully tightening the screws, ensure the detachable backrest and luggage rack attach properly. Refer to the instructions that came with each accessory before installing. NOTE: If the front mounting bushings are too wide for the backrest you can remove the thin washer between the mounting bushing and mounting bracket. Remove the screw holding the mounting bushing in place and remove the thin washer. Then reinstall. Make sure to use blue loctite on the screw threads and tighten securely. See FIGURE 3 .			
6.	When all accessories fit well then tighten the screws on each bracket. Be sure to recheck the tightness of the screws after the first ride and after the first 500 miles. See FIGURE 2 .			
7.	Re-install the saddle bags. REMOVE SCREWS	SLOT	RIGHT SIDE MOUNTING BRACKET	

$$\label{eq:relation} \begin{split} & \tilde{f} = 0 \\ & \tilde{f}$$

* Cobra® recommends you always wear a helmet while riding. Please never operate your motorcycle while under the influence of alcohol and/or drugs. Enjoy the new look of your motorcycle and please ride safely.



COBRA



