



INSTALLATION INSTRUCTIONS

BAG INSTALLATION: 50116-00, 50130-00



WARNING

Please read and understand these instructions completely before installation to avoid possible injury to yourself or damage to the accessory or vehicle. If you are unsure of your ability, seek the help of a qualified mechanic.



WARNING

Overloading any tank bag will result in a high center of gravity, which will cause bike to become top heavy and susceptible to unexpected tipping, especially on lean-in while negotiating high speed turns. MAXIMUM ALLOWABLE LOAD LIMIT IS 5 LBS.

1. INSTALLATION:

- ▶ Place and center magnetic unit directly on metal tank.
- ▶ Position to conform to tank profile and not to interfere with full left or right steering.

2. CARE & CLEANING:

- ▶ This product is supplied with a gasoline and scratch resistant rubberized layer. However, care should be taken to avoid gas spills and a heavy buildup of dust and/or dirt under the harness.
- ▶ Excessive dust and/or dirt may become embedded in the rubber, which may lead to scratches in the painted finish. Wiping with a mild bike wash detergent and applying a good quality wax will reduce the chance of scratching.
- ▶ Remove the bag before washing the bike.
- ▶ Use a mild detergent and soft brush to remove dirt or road grime from the bag. Rinse thoroughly and allow to air dry before using. Do not put in washer or dryer. Dry-cleaning is not recommended.

Note:

The [tank bag](#) is manufactured from heavy-weight water-proof polyester materials. However, in the event of heavy rain, moisture may enter the bags through seam or zippers. It is highly recommended that important papers, valuable items, or clothing be wrapped in plastic for added protection.