

	4.4[112]						
4 4							
2.48[63] 3.5[88]							

REVISION HISTORY						
REV.	DESCRIPTION					
01	PRELIMINARY RELEASE PER EC3410	2013-02-08				
02	REVISED PER EC3410	2013-02-27				
Α	INITIAL RELEASE PER EC3410	2013-03-04				

SPECIFICATIONS

1. CERTIFICATIONS: **(€**: ECE R10: IP67

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

- 2. LUMINOUS FLUX: 750 lumens
- 3. ILLUMINANCE: lux
- 4. PEAK BEAM INTENSITY: Candela
- 5. EFFICACY: 58.2 lm/W
- 6. CORRELATED COLOR TEMPERATURE: 5597K
- 7. VOLTAGE (NOMINAL): 12 to 24 VDC
- 8. VOLTAGE (EXTREME): 10 to 30 VDC
- 9. CURRENT (PEAK): 1.3A (@ 12 VDC NOMINAL)
- 10. POWER (MAXIMUM): 18.1W (@ 12 VDC NOMINAL)
- 11. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- 12. CONNECTION: 2 CONDUCTOR CABLE
- 13. MOUNTING: SINGLE BOLT
- 14. HOUSING MATERIAL: ALUMINUM
- 15. LENS MATERIAL: POLYCARBONATE
- 16. PRODUCT WEIGHT: X LBS (0.0 Kg)

NOTES: 1. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

NON DISCLOSURE ACREEMENT

NON DISCLOSURE AGREEMENT								
THIS DRAWING AND THE DESIGN IT DISCLOSES ARE THE RIVINE PROPERTY OF ECCO AND IS ISSUED IN COMPIDENCE FOR ENGINEERINGINFORMATION ONLY THE DRAWING AND JOE DESIGN MAY NOT BE LIBED, COPIED, EPERODUCED, OR OTHERWISE DESIGNOSED IN PART OR AS A WHOLE TO OUISIDERS OR USED FOR ANY OTHER PURPOSE WITHOUT THE PRIOR WITHEN CONSENT OF ECCO. THE DRAWING IS SUBJECT TO RECALL AT ANY TIME, YOUR POSSESSION OF THIS DOCUMENT CONSTITUTES ACCEPTANCE OF THESE TERMS, © 2013 ECCO.								

SCALE 1:1.5			APP	ROVALS	DATE						
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED:A			DRAWN BY A	ИDH	2013-02-27						
			CHECKED	BND	2013-02-28						
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES ARE:			MECH. ENG.	JLA	2013-02-27						
MILLIMETERS DECIMALS	IMETERS DECIMALS INCHES DECIMALS ANG ± 0.5		ELEC. ENG.	TJT	2013-02-27	WORK	LAMP, 6 LED, RE	CTANG	LE,FLOOD,10	0-30V	
XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	(± 0.1 (X ± 0.04 FRACTIONS	TEST ENG.	JRT	2013-03-01	CUSTOMER PAR			PRODUCT SERIES:		
		± 1/64	SALES.	WNH	2013-03-01	EW241	1		EW2411		
THIRD ANGLE PROJECTION						SIZE: A	DWG. NO.	EW24	11	REV.	
			Electronically Controlled Use Latest Copy			SHEET 1 OF 1	Project: EC3410	Date Cre	eated: 2013-02-08	Α	