

## Instructions: HONDA 02-07 CR125/250\*04-12 CRF250R/X

### 02-12 CRF450R/X (PMB-01-9004B)

This disc guard comes with a new wheel spacer and a mount to reinforce the stock mounting tabs on the brake caliper mount. To install this disc guard, please read the instructions carefully.

1. Remove the rear axle nut and the axle.
2. Remove rear wheel.
3. Remove the right side rear wheel spacer from the hub.
4. Install the supplied wheel spacer into the hub of the wheel.
5. Loosely install the new disc guard onto the stock mounting tabs on the brake caliper using two 6x14 socket head bolts. *(If the stock tabs are broken, install the new disc guard to the new mount reinforcement plate with two 6x14 socket head bolts. Use the broken stock tabs as a guide to determine which holes to use.)*
6. Loosen the 5x12mm set screw and install the guard mount reinforcement bracket onto the caliper mount with the set screw tab pointing out towards the swing arm and align the axle hole. Install two 6x14 socket head bolts at this time if not already installed. **DO NOT TIGHTEN ANY BOLTS YET!**
7. Re-install the rear wheel and the rear axle and nut (**do not tighten it all of the way!**).
8. Now would be a good time to adjust your chain if necessary.
9. Tighten the four 6x14 socket head bolts on the disc guard.
10. Remove the 5x12mm set screw and reinstall using a medium thread-locking agent. The set screw is to prevent rotation of the bracket if the stock tabs are missing or damaged. The set screw should only be inserted to provide a light contact with the caliper mount.
11. Re-check all bolts for tightness.

**CAUTION: Do not over-tighten set screw as this will bind the axle and prevent removal at a later date.**

#### Parts List:

1-Fin  
1-Bracket  
1-Spacer  
4-6x14 SH  
1-5x12 Set Screw