

INSTALLATION PROCESS:
FK003D214-2 Front Brake Line Kit
1999-2002 Yamaha YZF600 R6

Torque specifications
Stainless steel 15-17 ft. lbs
Aluminum 12-15 ft. lbs



Step 1:

Identify the key components that complete our brake line kit:

You should have two (2) lines, one (1) double banjo bolt, two (2) single banjo bolts, and one (1) c-clip. We have also included a total of nine (9) washers; seven (7) will be used, and two (2) will be spares. We strongly suggest having a professional mechanic install your brake lines, all other installs may void your warranty.

Step 2:

To ensure there is no paint damage from the brake fluid, completely cover the front end of the bike. Installing brake lines can be a messy process, and brake fluid *WILL* spill!

Step 3:

After bleeding and drying out the OEM brake system, uninstall your front stock hoses. Take note of how the stock system was routed in case you need to re-install the hoses.

Step 4:

Familiarize yourself with the new Galfer brake lines, *notice there is a right and left line, this is as if you are sitting on the bike*. Identify which ends to install to the front master cylinder. Install these lines to the master cylinder using a double banjo bolt and three (3) washers, the sequence will be as follows; master cylinder, washer, right line banjo fitting, washer, left line banjo fitting, washer, double banjo bolt. (See picture A)

Step 5:

Route the lines down to the lower triple tree. Use the OEM metal ring at the horn mounting bracket, keeping the lines close to the triple tree (See picture B) **OR** you may use the Galfer provided c-clip; by removing the "right" OEM bolt at the horn bracket, use the OEM bolt to keep the c-clip in place. Route the lines *behind the forks*

Step 6:

Remove the OEM line holders at your forks. Continue to route the lines down to their appropriate calipers. Install the lines using a single banjo bolt and two (2) washers for each caliper, the sequence will be as follows; caliper, washer, banjo fitting, washer, banjo bolt. (See picture C & D)

Step 7:

Before you begin the next step, please check the clearance of your new lines. When the front end is fully extended or compressed, make sure the lines do not bind with anything. Be sure to triple check that the lines are traveling correctly and are clear from any obstructions.

Step 8:

Bleed your brake system according to the owner's manual. Add Galfer DOT-4 brake fluid to the system and build appropriate pressure.

Step 9:

Once you have bled the system, please check the brake fluid level in your master cylinder. Top off your brake fluid according to your manual and close the brake fluid reservoir. To ensure there are no leaks or other issues, zip-tie the brake lever to the throttle for at least 2 hours. If the lines are not leaking and all else looks good, (bolts are tight and torqued down to specification, washers are in place, and lines are clear from obstruction) you are now ready to ride with the new brake system.

Please be aware that the overall braking feel has been changed dramatically. We suggest taking it easy while you get used to the new brake lever pressure and feel. We recommend checking your brake system periodically; be sure to check that your bolts are tight and *VERY* carefully check your lines for any leaks or damage. If there are any signs of damage or stress to the lines, the complete brake line kit will need to be replaced. Remember, our brake lines have a **LIFETIME WARRANTY!**



A. Master Cylinder



B. Stock ring at lower triple tree



C. Right Caliper



D. Left Caliper