



DRY-16XSR9-K

Dash Relocator 2016 Yamaha XSR900

<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>

- 1) Remove the 3 . 4mm allen head screws on the back of the gauge. **Photo 1**



PHOTO 1

- 2) Pull the gauge out while it's still plugged in. Once the gauge is out of the stock mount, pull back the rubber plug cover and unplug the harness from the gauge. Push the harness through the gauge mount. **Photo 2.**



PHOTO 2

- 3) Remove the 4mm allen head bolt holding the cable guide in place. Then remove the 2 . 5mm allen head bolts holding down the gauge mount.
- 4) Install the rubber gauge mount onto the Graves Dash Relocator mount.
- 5) Install your new Graves Dash Relocator in the reverse order that you removed the stock mount.

Must haves for your new 2016 XSR900

Clean things up with a Graves Fender Eliminator



FEY-16XSR9-K

Add a Full Titanium Exhaust System
to your XSR900 for optimum performance



**2016 XSR Full Titanium Exhaust
EXY-14FZ09-FTT**

The purchaser releases Graves Motorsports, Inc. from all liabilities pertaining to the installation and use of purchased parts. Purchaser recognizes that any alteration and/or modifications to the vehicle may increase the risk of injury or accident. **This product is intended for Closed Course Competition Use Only** and may render the vehicle illegal for use on public roads.