

FEY-16FZ10-K

Parts List:

- Fender Eliminator Bracket Assy
- 6 x 25mm Allen Bolts

Fender Eliminator 2016 Yamaha FZ10

Rubber Grommet

1

<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>

- 1) Remove the seat using the key.
- 2) Remove the rear cowl by removing the 2- 10mm bolts, 4- 6mm allen head bolts, 1- 4mm allen head bolt and the 4 push pins underneath.
- Remove the seat lock assembly by removing the 4-8mm bolts. Photo 1. Unplug the turn signals and the license plate light.



Photo 1

4) Remove the rear fender assembly by removing the 4- 10mm nuts. **Photo 2**. Once you have it loose, hold it with one hand and finish removing the 4 nuts. Lower the fender down carefully pulling the wiring through the tail section.



Photo 2

5) Reinstall the stock turn signals into the Graves fender eliminator bracket. Run the turn signal wires through the hole on the fender eliminator bracket and then install the rubber grommet to close off the hole. **Photo 3**.



Photo 3

- 6) Using the 4- 6x25mm bolts supplied and the 4 stock locking nuts, install the Graves Fender Eliminator in the reverse order that the stock bracket came off.
- 7) Once the Graves Fender Eliminator kit has been installed, turn the motorcycle on and ensure the turn signals are installed correctly and are functioning properly. Reinstall the seat lock assembly, rear cowl and the seat.

Must haves for your new 2016 FZ10

Clear, Flush Mount Marker Lights compliment your new Fender Eliminator

TS401C1

