

FSK-11ZX1-K

PARTS LIST

Long Slider Puck

- Short Slider Puck
- Long Spacer
- Short Spacer
- Large Washer

Frame Sliders - Black 2011 Kawasaki ZX-10

2

1

1

1

1

- Small Washer
- 90 x10 x17m hex head bolt
- 35x10 x17m hex head bolt
- 65x10x14m hex head bolt
- Stop nut slider puck adapter

NOTE: Remove O-Ring before Installation NOTE: Install one side at a time

1

1

1

1

2

Left Side

- 1. Remove the engine mounting bolt
- 2. Install the 90mm bolt through the small washer, spacer, long puck, large washer, frame and into the engine case. NOTE: Locktite Is Recommended
- 3. Torque to factory specifications

Right Side

<<<<< IT IS RECOMMENDED THAT THIS PRODUCT BE INSTALLED BY A QUALIFIED TECHNICIAN >>>>>>

- 1. Remove the engine mounting bolt.
- 2. Install the 65mm engine bolt. Torque to factory specifications NOTE: Loctite is recommended.
- 3. Using a spanner wrench or drift, remove the stop nut.
- 4. Install the stop nut frame slider adapter. Torque to factory specifications.
- Install the 35mm bolt through the small washer, spacer, puck and large washer. Torque to 38ft lb/52Nm.