

WHA9697 ADAPTER

KIT CONTENTS

- 1 - WHA9697 RADIO ADAPTER HARNESS
- 2 - 15 AMP ATC FUSE(S)



INSTALLATION INSTRUCTIONS

1. WITH THE IGNITION SWITCH OFF, REMOVE THE FRONT FAIRING COVER, NOTING WHICH HOLE EACH SCREW IS REMOVED FROM.
TIP: REFER TO MANUFACTURER INSTRUCTIONS IF NECESSARY, AND DON'T FORGET TO COVER YOUR FENDER.
2. GAIN ACCESS TO THE MAIN FUSE PANEL, AND REMOVE THE 2 FUSES LABELED RADIO POWER (10A) AND RADIO MEMORY (1A).
TIP: REFER TO MANUFACTURER INSTRUCTIONS IF NECESSARY.
3. DISCONNECT THE 2 DEUTSCH CONNECTORS FROM THE STOCK WIRING AND REMOVE THE RADIO.
NOTE: IF INSTALLING NEW SPEAKERS, REPLACE THEM NOW.
4. INSTALL THE WHA ADAPTER HARNESS BY CONNECTING THE 2 DEUTSCH CONNECTORS (8 AND 12 PIN) TO THEIR APPROPRIATE HARNESS CONNECTORS.
5. INSTALL NEW RADIO OR SOURCE UNIT INTO THE FAIRING, AND CONNECT TO THE WHA ADAPTER HARNESS MAIN CONNECTOR (23 PIN).
TIP: REFER TO MANUFACTURER INSTRUCTIONS IF NECESSARY.
6. INSTALL THE 2 15A ATC FUSES INCLUDED WITH THIS KIT IN THE RADIO POWER / RADIO MEMORY SLOTS OF THE MAIN FUSE PANEL.
NOTE: MAKE SURE THAT YOUR POLARITY IS CORRECT (+/- MATCHES ON ALL SPEAKERS).
7. TURN THE KEY TO THE ACCESSORY POSITION AND VERIFY THAT THE NEW RADIO OR SOURCE UNIT FUNCTIONS PROPERLY.
8. RE-INSTALL THE FAIRING COVER.
TIP: REFER TO MANUFACTURER INSTRUCTIONS IF NECESSARY.