



WARNING!

Prior To Installation Clean Tank Interior Thoroughly. Install This Fuel Tank ONLY In a Well Ventilated Area, As Gasoline Fumes Are EXTREMELY Dangerous. DO NOT START OR OPERATE THE VEHICLE IF THERE ARE ANY FUEL LEAKS!

IMS Recommends That Installation Be Done By a Licensed Mechanic. Improper Installation May Result In Severe Bodily Injury Or Death. Read All Instructions Prior To Installation.

KTM

FUEL TANK:

3.7 GALLONS

IMS Tank ID: KTM-16

IMS Part no.

113326/213326

Fits 2-STROKE ONLY

KTM: (07-08') SX125-250

KTM:(2008') 200/300

XC / XC-W (e)

Does fit (e) elec-start

No spark plug access

IMS PARTS LIST

- (1) Fuel Tank
 - (1)*Gas Cap & Seal
 - (1) Seat Tongue Bracket
 - (10) 5x12 with 8mm Head 12mm Flange Bolts
 - (2) 5x12mm Phillips Head Screws
 - (1) 6" Fuel Line
- *Excluded On Dry-Break**

OEM ITEMS TO USE

- Fuel Line (some models)
- Petcock
- Shrouds

TANK REMOVAL

Drain all fuel from OEM fuel tank into a government approved fuel container with a greater capacity than fuel tank on vehicle.

Remove seat, fuel line at petcock, shrouds, and tank bolt (center mount). Remove OEM Tank and Petcock.

TANK INSTALLATION

Mount seat tongue bracket to tank. Install OEM petcock using the **IMS** 5x12mm flange bolts. Fit tank on the vehicle, install center-mounting bolt.


Be sure that the tank is mounted securely and does not bind or in any way inhibit the controls or function of the vehicle. Ensure that there are no sharp objects that rub against the tank that may eventually puncture the tank. Check that you have sufficient clearance from any heat source that could melt the fuel tank.

Attach the Shrouds to the Radiators and Then Attach the Shrouds to the Tank With the 5 x 12mm Bolts Supplied. Use the Two 5x12mm Phillips Head Screws to attach the Shrouds at the top inserts by the tank center mount, under the seat. These low profile and smooth screw heads will help prevent Seat Cover damage. Attach the Seat.

If the OEM Fuel Line is Too Short or if it will Kink after connection Install the Fuel Line Supplied after cutting to the proper length for your Model.

Turn the Petcock to the Closed Position and fill your new **IMS** fuel tank. Always check for any fuel Leaks Before Operating your Bike and Enjoy your Longer Ride!

Mount Bracket This Side Up.



"FOR COMPETITION USE ONLY"

"Legal in California ONLY for racing vehicles which may never be used upon a highway?"

DISCLAIMER:

Due to uncontrolled variables in the manufacturing process of rotationally molded fuel tanks, the fuel tank may vary in size and shape by up to 7% of the manufacturer's original listed capacity