



ROKKER® XXR
6.71" Fairing Speaker Upgrade
Kit for 2015-2019 Harley®
RoadGlide/Ultra

#HRRK-6712TW-RXX

Installation
Instructions

Product Overview

J&M's ROKKER XXR series 6.71" speakers designed as exact size component/replacements for the stock 6.5" Harley fairing speakers as installed on the 2014-2019 Harley RoadGlide Ultra.

Spec'd at 2 ohms impedance and 300 watts maximum input (175w RMS - 91db sensitivity), speakers provide the ultimate in raw audio power and include the new custom grills with built-in high-output tweeters.

Lightweight waterproof one-piece woven-fiber driver cone with super-rigid metal basket design.

High-density lite-weight Neodymium magnet structure, specially coated to maintain flux-strength integrity even at extreme operating temperatures.

High efficiency VENTED voice-coil for improved cooling when operating at high volume levels for extended periods.

Custom speaker grills with high-output tweeters for crystal clear sound at highway speeds.

Mounting hole pattern and spade electrical connections are exactly the same as the factory specification, this is a total plug-and-play no-modification solution complete with easy to follow installation instructions.

These are THE most powerful speakers you can buy for your Harley and they will perform extremely well when used with a medium to high-powered accessory amplifier.

Installation and Instructions

1. Remove the stock fairing grills by gently prying up the inner edge of each grill & pull outward. **(Fig. A)**
2. Remove the 4 torx attachment screws from each stock speaker, unplug the wires from the rear and remove both speakers from the fairing pods. **(Fig. B)**
3. Install the new 6.71" ROKKER XXR speakers using the original-speaker attachment screws; Ensure that the speaker is placed into the pod with the tweeter-wire plug exiting to the upper, outer corner. **(Fig. B)**
4. Install new ROKKER grill by first plugging in the backside tweeter wire to the speaker, then place into position and press down until locked at all four corners. **(Fig. C)**
5. Then from the top side of each mounted speaker, behind the grill, pull the EXTRA tweeter wire length back out between the back side of the grill and front of the main speaker, so that this extra wire does not rattle against the main speaker cone when playing.

Thank you for the confidence you have shown in J&M Corporation by purchasing one of our innovative products.

