



**WARNING!** Helmet speakers may not be legal in all jurisdictions. Check your local laws BEFORE using this product. J & M Corporation cannot control the circumstances surrounding the sale of this equipment, the quality of installation, or the specific helmet into which this equipment is installed. Accordingly, J & M Corporation makes no warranties, expressed or implied, related thereto. A helmet with this equipment installed may not protect the user from injury. The user assumes all liability in conjunction with accidents, injuries or losses of any kind arising out of the use of this product. Additionally, this product should not be used in any way that would impair the user's ability to hear traffic or other noises. Accordingly, the volume should be kept low or off, depending upon the circumstances.

# Slide-in Shorty-Style Helmet Headset Installation Instructions

1.) Begin by inserting the small center tab on the headset into the back of your helmet between the interior and outer shell of your helmet. **See Figure 1.**

2.) Insert the large tab on the left side of the headset into your helmet in the same manner making sure that the headset is on the inside of the retention strap on your helmet. **See Figure 2.**

3.) Repeat this procedure for the right side.

4.) Reposition both sides of the headset as necessary so that both speakers are correctly positioned over your ears.

5.) After proper positioning of the speakers is accomplished, route both helmet straps through the small retention loops on both sides of the headset. **See Figure 3.**

6.) Pull the small, medium or large windsock (your preference) over the microphone.

7.) Use the correct Z-Series or P-Series lower section hook-up cord (sold separately) to connect this headset to your particular motorcycle audio system.

