



**Saddlebag-Lid Kit
w/ROKKER® XXR 5X7”
Speakers & Plug-n-play Wiring
Harness Included for
1998-2013 Harley® Baggers**

#HSBL-065X7-XXR

**Installation
Instructions**

Product Overview



This complete custom saddlebag-lid kit with ROKKER XXR 5X7" speakers, custom grills & Harley spec plug-n-play wiring harnesses included, has been designed for the 1998-2013 Harley® Bagger saddlebags.

Saddlebag lids are finished in Harley spec color "Vivid-Black" and can be special ordered in many standard 98-13 Harley factory colors for an extra.

This mount-from-the-top speaker/lid design is identical to factory Harley and makes for a water tight seal under the speaker itself, so that moisture is never allowed to enter the saddlebag.

J&M's **NEW** ROKKER XXR series 5X7" speakers are spec'd at 2 ohms impedance and an impressive 300 watts maximum power (175w RMS - 91db sensitivity), and are weatherproof from the top with their one piece carbon fiber cone and bridge mounted high-output dome tweeter.

These are THE most powerful 5X7" speakers you can buy for your Harley and the on-highway performance will exceed that of most 6X9 speakers available in the marketplace today.

Installation Instructions

1. If you are going to initially install these saddlebag lids without painting them, clean the underside of the lid seat area with alcohol, and apply the molded rubber seal all the way around the underside lip of each bag lid.
2. If you going to have them painted, prior to installation, remove first the speakers and grills from each lid and have them painted to the color of your choice. Then install the molded rubber seal and latch striker plates to the lids, prior to continuing on to step #3.
3. Remove both left and right stock saddlebag lids and latch assemblies from the saddlebags.
4. Remove both saddlebags, side covers, seat and fuel tank.
5. Remove the latch assembly from the left side factory saddlebag lid and install it on to the left side J&M ROKKER XXR series lid assembly.
6. Carefully drill a 5/16" diameter hole in the bottom of the left saddlebag in the location shown. **Diagram A**
7. Install the provided rubber grommet into the hole. Then, from the inside of the saddlebag, route the left side speaker harness (brown/ white-brown) through the grommet and install the pins into the provided plastic connector onto the speaker harness. **IMPORTANT: BE SURE TO INSERT THE CORRECT WIRES INTO THE CORRECT LOCATION IN THE PLASTIC CONNECTOR.** **Diagram B**
8. Reinstall the left saddlebag onto the motorcycle.
9. Install the left side J&M lid assembly onto the left saddlebag.
10. Connect the wire terminal plug to the connector socket of the J&M 5X7" ROKKER XX speaker and route the speaker harness underneath the saddlebag lid tether strap and along the inside of the saddlebag as shown. **Diagram C**
11. Connect the forward section of the saddlebag lid speaker harness to the in-line wire plug and route the harness along the frame, under the fuel tank, and into the fairing. Secure the harness using the provided tie-straps.
12. Repeat the entire process for the right side saddlebag assembly.
13. Reinstall the fuel tank, seat, and side covers.

