



ROKKER Series Tweeter Kit

For 1998-2013 Harley® Dresser

Part#HTWT-1025-CRT

**Installation
& Operation
Instructions**

Product Description

This exciting new J&M ROKKER series tweeter kit has been design specifically for use on the 1998-2013 Harley® Ultra-Class (BatWing) or RoadGlide style fairing.

These are 25mm diameter high-output dome tweeters designed to bring extra high-frequency definition to your Harley Bagger audio system.

Tweeters are spec'd at 2 ohms nominal impedance, and will work with any radio or amplifier designed to operate at a 2, 4, 6 or 8-ohm load.

Rated at 300w peak power (150w RMS), 3,000 - 21khz frequency range, & 94db sensitivity @ 1w, 1m, these tweeters can easily replace

two of the stock Harley gauges on the inside fairing panel.

These new 'J&M ROKKER series tweeters will connect direct to the midrange output jack on the back of the 'J&M ROKKER series speaker crossover network, OR to the front speaker spade connections inside the fairing, using the custom made plug-n-play wiring harnesses included.

This kit includes 2 tweeters, alternate connection wire assemblies, along with all necessary mounting hardware & complete installation instructions.

Installation Instructions

1. Remove the outer fairing shell.
2. Remove both lower gauges next to the radio, retain the gauge cups and nuts to be used on the tweeters.
3. Install the tweeter using the previously removed gauge cups and nuts.

4a. Connect the tweeters to the speaker wires between the radio head unit and the main fairing speakers, or between the radio head unit and booster amplifier inputs, with the Y-wire harness plugs provided.

OR

4b. Connect the tweeters using the attached white two pin connectors, to the midrange crossover plug on the back of the J&M ROKKER or ROKKER XT speakers.

Thank you for the confidence you have shown in J&M Corporation by purchasing one of our innovative products.



Learn more about motorcycle sound systems we have.