


Jardine

EXHAUST SYSTEMS


17-2903-01

**Yamaha Virago XV700/750/1000/1100
DRAG PIPES**



Parts Included

Front and Rear Drag pipes



Hardware Included

- 1) 3/8"-16 x 3/4" LG Hex Head Bolt
- 1) 3/8" Lock Washer

Tools Required

- Ratchet
- 9/16" Socket/Wrench



Installation

1. Place bike on center stand.
2. Remove rear right peg. Loosen front muffler by unbolting stock clamp.
3. Loosen clamp that connects lower muffler to rear cylinder head pipe. Remove stock mufflers.
4. Remove rear cylinder flange nuts. Open ring that holds the headpipe to the flange then remove head pipe.
5. Remove front cylinder flange nuts. Remove front head pipe.
6. Install rear Jardine drag pipe first. This will take a little effort on your part for a proper fit. You must start with the pipe pointing straight out at a 90° from the bike. You may have to work the flange between the engine case and the frame in the same place that the stock pipe was remove from. (NOTE: If Jardine forward controls have been installed, you must loosen up rear brake spline and the rear nut before installing the drag pipes.)
7. Locate lower drag pipe to front cylinder head. Finger tighten with stock flange nuts.
8. Using supplied 3/8"-16 x 3/4" LG hex head bolt and 3/8" lock washer, attach lower drag pipe to top drag pipe - finger tighten at this time.
9. Align system as desired and tighten all bolts and nuts.

A HISTORY OF QUALITY AND PERFORMANCE SINCE 1959

Learn more about motorcycle parts on our website.