



## PARTS INCLUDED

- 1 - Supersport Fender
- 3 - M6-1.0x25mm Socket Button Head Bolts
- 3 - Nylon Mounting Spacers

## TOOLS REQUIRED

- Ratchet
- 10mm Socket
- 12mm Socket
- 14mm Socket
- 4mm Allen Socket

46-3005-03

SUPERSPORT FENDER KIT

KAWASAKI ZX-14  
2006-07

---

## INSTALLATION INSTRUCTIONS

- 1) Remove the passenger seat. Remove the tool kit and any other equipment you may have in the trunk area.
- 2) Disconnect the license plate light plug inside the trunk area.
- 3) Remove the three bolts securing the original rear fender/license plate mount to the tail section. Remove the rear fender.
- 4) Place the supplied mounting spacers between the new Supersport Fender Bracket and the tail section of the motorcycle. Secure the new bracket to the motorcycle using the three supplied M6-1.00x25mm button head bolts. Tighten bolts to 9.5 lb-ft.
- 5) Reinstall the rider seat and passenger seat (or rear cowl).
- 6) Turn on the motorcycle and make sure all lighting and turn signals are working properly.
- 7) Mount your license plate to the Supersport Fender.

---

PERFORMANCE DELIVERED!

Learn more about motorcycle parts on our website.