

TECHNICAL SPECIFICATIONS

US PART #	WHEEL	SIZE	TT/TL	LOADING SPEED INDEX	O.D. (IN)	S.W. (IN)	MAX LOADING (LBS)	MAX PSI	TREAD DEPTH (MM)	WEIGHT (LBS)
047851203B0	REAR	80/100-12	TT	41M	18	3	319	20	13.00	5.21
047851401B0	FRONT	60/100-14 (250-14)	TT	30M	19	2	233	20	9.00	3.76
047851404B0	REAR	90/100-14 (3.00/4.10-14)	TT	49M	21	4	407	20	13.50	7.29
047851604B0	REAR	90/100-16 (3.00/4.00-16)	TT	52M	43	4	440	20	13.50	8.21
047851702B0	FRONT	70/100-17 (2.50/2.75-17)	TT	40M	22	3	308	20	9.50	5.10
047851902B0	FRONT	70/100-19 (2.50-19)	TT	42M	24	3	330	20	9.50	5.77
047851811B0	REAR	110/100-18 (425/450-18)	TT	64M	26	5	616	20	16.00	11.85
047851813B0	REAR	120/100-18 (510-18)	TT	68M	27	5	693	20	16.00	13.08
047851906B0	REAR	100/90-19	TT	57M	26	4	506	20	16.00	13.00
047851923B0	REAR	110/80-19	TT	59M	26	4	535	20	16.00	12.95
047851910B0	REAR	110/90-19	TT	62M	27	5	583	20	16.00	12.69
047851975B0	REAR	120/80-19	TT	63M	26	5	598	20	16.00	12.07
047852104B0	FRONT	80/100-21 (300-21)	TT	51M	28	3	429	20	12.00	8.77
047852130B0	FRONT	90/100-21	TT	57M	27	3	506	20	12.00	8.77