

PS692 | PS694



PS69 Coaxial Speakers Owner's Manual

PERFORMANCE

Woofer Size | in [mm] 6 x 9 [150 x 230]

Tweeter Size | in [mm] 1 [25]

Frequency Response | Hz 40-20,000

Max Recommended Amplifier Power [Watts] | PEAK/RMS 180/90

Sensitivity [SPLo] | dB @ 1W, 1m 87.2

Nominal Impedance [Zn] | ohm 2Ω (40PS692), 4Ω (40PS694)

Weight | oz [g] 43.5 [1234]

Mounting Hole Diameter | in [mm] 5 5/8 x 8 7/16 [143 x 214]

 Mounting Depth | in [mm]
 3 1/4 [83]

 Top Mount Height | in [mm]
 7/8 [23]

Package Contents:

(2) PS69 Speakers

(8) M4 x 25mm pan cross head woodscrews

(4) 22ga, red crimp-style butt connectors

(2) Kicker badges


(2) 12" wiring harnesses

(8) M4 speed nuts

(2) Grilles

WIRING

We recommend using 16 gauge (or larger) wire. The PS Speakers are rated at 2 or 4 ohms. **Make sure you match the speaker impedance with the amplifier load rating.**



Two PS Speakers wired in parallel to a single channel

WOOFER MOUNTING

The KICKER PS Speakers are all-purpose, weather-proof and ready to meet the demands of any environment. When possible, mount the speakers in a vehicle's factory locations or in a location with a semi-isolated rear chamber, such as saddle-bad lids on your motorcycle

Custom mounting locations will require more preparation and work. Make sure that the speaker will not interfere with trunk and door opening and closing mechanisms and that the enclosed screws will not puncture the fuel tank, puncture wiring, or interfere with any other mechanical parts on the underside of the mounting surface. If you're installing the speakers in a door, cycle the windows all the way down and up.

If the speaker cut-out locations require you to cut metal, avoid structural metal and braces.



Mount the speakers to desired location using the included screws

Pro Tip: You're a KICKER PX amplifier and a few cables away from a full system upgrade! KICKER PX amps provide audio-connectivity and low current draw for an easy install that won't tax your electrical system.