

2-STROKE SYNTHETIC LUBRICANT

R-50® TechniPlate®

Klotz R-50 is a pure synthetic lubricant designed exclusively for use in all sustained Hi-RPM 2-stroke racing engines. R-50 film strength is comparable to castor oil with the benefits of Clean Burn Technology®.

- TechniPlate® lubricity system for superior film strength and anti-scuff protection
- Extreme Load Carrying Capacity to eliminate bearing and ring wear
- Clean Burn Technology reduces carbon and residue build-up
- Contains familiar Klotz Red-Smells like Klotz™
- Anti-Oxidation protection against rust and corrosion
- Power Valve formula



CHARACTERISTICS

Film Strength 10 Scale 1 = Failure - 10 = No Wear

Pour Point -9°F Flash Point 550°F Maximum RPM Unlimited

Viscosity @ 100°C 16.30 cSt Min 21.90 cSt Max 18.20 cSt Typical

Product Color Red

Chemical 100% Pure Synthetic

Biodegradable 42%

CERTIFICATIONS

A.P.I. S.A. Intended for racing engines only

DIRECTIONS

MX and Dirt Track: Water-cooled engines 60-125cc mix at 32:1,

250+cc mix at 40:1 to 50:1

ATV: Water-cooled mix at 40:1, Air-cooled engines mix at 32:1

Kart: Air-cooled mix at 20:1 to 25:1 **Shifter Kart:** Liquid-cooled mix at 32:1 **PWC:** Full mod mix at 40:1 to 50:1

Snowmobile: Full mod mix at 40:1 to 50:1 **R/C Model:** 2-Stroke gas mix at 20:1 to 32:1

2-Stroke pre-mix: DO NOT use in oil injection systems.

COMPATIBILITY

Blends with gasoline and stays in suspension. Will blend with petroleum oils and some synthetic lubricants.

Will not blend with alcohol.

Will blend in gasoline at ratios of 15:1 or greater.

PART NUMBERS

 KL-102
 10 PT CASE

 KL-104
 10 QT CASE

 KL-105
 4 GAL CASE

 KL-104 30 GL
 30 GAL DRUM

 KL-104 55 GL
 55 GAL DRUM

RECOMMENDED APPLICATIONS

Motorcycle/ATV:

Hi-performance Racing 10K RPM+ Snowmobile:

Drag Racing, Snow Cross 9500 RPM+

PWC:

Racing 10K RPM+

<u>Kart/Micro Sprint:</u> Hi-performance Racing 10K RPM+

R/C Modeling:

Gasoline 30-45K RPM