



## 2-STROKE SYNTHETIC LUBRICANT

### Snowmobile TechniPlate® TC-W3

Klotz sets the standard for power and reliability. Snowmobile TechniPlate® TC-W3 provides extreme high load carrying capacity for reduced engine wear and low maintenance. Clean Burn™ No-Smoke technology eliminates carbon and residue build-up. Warranty compliant for all major manufacturers including Ski-Doo®, Polaris®, Yamaha® and Arctic Cat®.

- Improves throttle response
- TechniPlate lubricity system for superior film strength and anti-scuff protection
- Clean Burn™ for low smoke and prevents plug fouling
- Anti-Oxidation [protection against rust and corrosion
- Identifiable Klotz Red for easy mixing - Smells Like Klotz
- Power valve formula
- Super cold pour point of -40°F provides fast, easy starting
- Pre-mix or oil injection



#### CHARACTERISTICS

Smoke Rating	10	Scale 1 = Fog - 10 = No Smoke
Clean Burn™	10	Scale 1 = Heavy Deposits - 10 = No Carbon
Film Strength	8	Scale 1 = Failure - 10 = No Wear
Pour Point	-40°F	
Flash Point	275°F	
Maximum RPM	10,000	
Viscosity @ 100°C	6.5 cSt Typical	
Product Color	Red	
Chemical	100% Pure Synthetic	
Biodegradable	48%	

#### CERTIFICATIONS

API TC	TC-W	NMMA TC-W3
JASO FD	ISO-EGD	RL#93101 DFI

#### DIRECTIONS

Pre-mix: 40:1 to 50:1  
Refer to engine manufacturer's recommendation  
Oil Injection: Pour directly into tank

#### COMPATIBILITY

Gasoline  
\*Stays in suspension  
Fuel Stability: Will blend in gasoline at ratios of 15:1 or greater  
Blends with petroleum and most synthetic oils

#### PART NUMBERS

KL-215	10 QT CASE
KL-216	4 GAL CASE
KL-215	5 GAL PAIL
KL-215	30 GAL DRUM
KL-215	55 GAL DRUM

#### RECOMMENDED APPLICATIONS

2-Stroke Snowmobile

Stock

Trail

Hi-Performance

Drag Racing

Snow Cross

Water Cross