



2-STROKE SYNTHETIC LUBRICANT

Motorcycle TechniPlate® TC-W2

Specifically designed for 2-stroke hi-performance engines. Formulated to provide superior film strength with the clean-burning characteristics of Klotz Synthetic Lubricants. Klotz Motorcycle TechniPlate® TC-W2 will challenge and outrun the competition in the following ways:

- **Improves throttle response**
- **TechniPlate® lubricity system for superior film strength and anti-scuff protection**
- **Clean-Burn™ for low smoke and prevents plug fouling**
- **Contains familiar Klotz Red-Smells Like Klotz™**
- **Recommended for power valve engines**
- **Premix or oil injection systems**
- **JASO FC certified**



CHARACTERISTICS

| | | |
|-------------------|---------------------|--|
| Smoke Rating | 9 | Scale 1 = Fog - 10 = No Smoke |
| Clean Burn™ | 10 | Scale 1 = Heavy Deposits - 10 = No Carbon |
| Film Strength | 8 | Scale 1 = Failure - 10 = No Wear |
| Pour Point | -40°F | |
| Flash Point | 275°F | |
| Maximum RPM | 10,000 | |
| Viscosity @ 100°C | 7.10 cSt Typical | |
| Product Color | Red | |
| Chemical | 100% Pure Synthetic | |
| Biodegradable | 43% | |

CERTIFICATIONS

JASO FC, API TC

DIRECTIONS

2-Stroke pre-mix or oil injection

Motorcycle: Mix at 32:1 to 40:1

COMPATIBILITY

Blends with gasoline and stays in suspension. Will blend with petroleum oils and some synthetic lubricants.

Will not blend with alcohol .

Will dissolve in gasoline ratios of 15:1 or greater.

PART NUMBERS

| | |
|--------------|-------------|
| KL-300 | 10 QT CASE |
| KL-301 | 4 GAL CASE |
| KL-300 55 GL | 55 GAL DRUM |
| KL-300 30 GL | 30 GAL DRUM |

RECOMMENDED APPLICATIONS

Motorcycle/ATV:

Stock

Trail

Hi-Performance

Racing

Rely only on high-grade motorcycle oils & chemicals offered on our virtual shelves.