



2-STROKE SYNTHETIC LUBRICANT

Motorcycle TechniPlate® TC-WII

Specifically designed for 2-stroke hi-performance engines. Formulated to provide superior film strength with the clean-burning characteristics of Klotz Synthetic Lubricants. Klotz Motorcycle TechniPlate® TC-WII will challenge and outrun the competition in the following ways:

- **Improves throttle response**
- **TechniPlate® lubricity system for superior film strength and anti-scuff protection**
- **Clean-Burn™ for low smoke and prevents plug fouling**
- **Contains familiar Klotz Red-Smells Like Klotz™**
- **Recommended for power valve engines**
- **Premix or oil injection systems**
- **JASO FC certified**



CHARACTERISTICS

Smoke Rating 9	Scale 1 = Fog - 10 = No Smoke
Clean Burn™ 10	Scale 1 = Heavy Deposits - 10 = No Carbon
Film Strength 8	Scale 1 = Failure - 10 = No Wear
Pour Point -40°F	
Flash Point 275°F	
Maximum RPM 10,000	
Viscosity @ 100°C 7.10 cSt Typical	
Product Color Red	
Chemical 100% Pure Synthetic	
Biodegradable 43%	

CERTIFICATIONS

NMMA TC-WII, JASO FC

DIRECTIONS

2-Stroke pre-mix or oil injection

COMPATIBILITY

Blends with gasoline and stays in suspension. Will blend with petroleum oils and some synthetic lubricants.

Will not blend with alcohol .

Will dissolve in gasoline ratios of 15:1 or greater.

PART NUMBERS

KL-300	10 QT CASE
KL-301	4 GAL CASE
KL-300 55 GL	55 GAL DRUM
KL-300 30 GL	30 GAL DRUM

RECOMMENDED APPLICATIONS

Motorcycle/ATV:

Stock
Trail

Hi-Performance
Racing