



## 2-STROKE SYNTHETIC LUBRICANT

### 50:1 2-Stroke TechniPlate® TC-W3

50:1 TechniPlate® TC-W3 is a pure synthetic lubricant. It has an extremely high load carrying capacity for reduced engine wear. Clean Burn™ No-Smoke Technology eliminates carbon and residue build-up. Meets and exceeds JASO FD, ISO-EGD, TC-W, NMMA TC-W3 and API TC specifications for certified warranty compliance. Klotz 50:1 TechniPlate® TC-W3 will challenge and outrun the competition in the following ways:

- **TechniPlate® lubricity system for superior film strength and anti-scuff protection**
- **High load Carrying Capacity for reduced bearing and ring wear**
- **Clean Burn™ Technology eliminates carbon and residue build-up**
- **Ashless, No smoke formula provides cleaner exhaust**
- **Contains familiar Klotz Red for easy mixy and racy color**
- **Anti-Oxidation protection against rust and acorrosion**



#### CHARACTERISTICS

Smoke Rating	10	Scale 1 = Fog - 10 = No Smoke
Clean Burn™	10	Scale 1 = Heavy Deposits - 10 = No Carbon
Film Strength	8	Scale 1 = Failure - 10 = No Wear
Pour Point	-38°F	
Flash Point	275°F	
Maximum RPM	10,000	
Viscosity @ 100°C	7.40 cSt Typical	
Product Color	Red	
Chemical	100% Pure Synthetic	
Biodegradable	48%	

#### CERTIFICATIONS

Klotz certified warranty compliant when a JASO FD, ISO-EGD, API TC, TC-W or NMMA TC-W3 (RL# - 93101) lubricant is required.

#### DIRECTIONS

2-Stroke pre mix or oil injections:40:1 · 50:1 Use in any 2-stroke application that calls for API TC, TC-W2 or TC-W3 lubricant.

Will suspend in gasoline at ratios of 15:1 or greater.

#### COMPATIBILITY

Blends with gasoline and stays in suspension.

Will blend with petroleum oils and synthetic lubricants

#### PART NUMBERS

KL-305	10 PT CASE
KL-305 30 GL	30 GAL DRUM
KL-305 55 GL	55 GAL DRUM

#### RECOMMENDED APPLICATIONS

Moped: 2-Stroke/gas

Motorcycle: 2-Stroke/gas; stock, trail, Hi-performance

Snowmobile: 2-Stroke/gas; Stock, Hi-performance

Marine: 2-Stroke/gas; Stock, Hi-performance

PWC: 2-Stroke/gas; Stock, Hi-performance