




## 5W Racing Fork Fluid

Klotz Racing Fork Fluid exceeds manufacturers specifications for cartridge and standard racing forks. Blended from the finest synthetic hydraulic fluids to match racing for system specifications. Klotz racing Fork Fluid retains its viscosity over extreme temperature ranges to provide consistent and reliable dampening control under all weather and competition conditions.

- **Zero drag formula gives superior control**
- **Thermally stable viscosity in extreme heat and cold**
- **Non-foaming fluid eliminates fading**
- **Anti-wear properties extend fork life**
- **Seal conditioner prevents seal hardening**



### CHARACTERISTICS

Film Strength	8	1 = failure - 10 = no wear
Pour Point	-20°F	
Flash Point	400°F	
Viscosity @ 100°F	4.30 cSt Typical	
Product Color	Red	
Chemical	100% Pure Synthetic	
Biodegradable	42%	

### CERTIFICATIONS

None

### DIRECTIONS

Follow manufacturers' recommendations. Lighter weight Klotz Racing Suspension Fluids offer less dampening and a softer ride; while heavier weights provide increased dampening and a firmer ride. Match viscosity to riding conditions. Available in 5W, 10W, and 15W. Klotz Racing Fork Fluid can be blended together to achieve a specific viscosity. Klotz 5W Racing Fork Fluid replaces Showa SS-7M and Kayaba Spec. 01 fork oils.

### COMPATIBILITY

Will blend with petroleum and synthetic fork/shock fluids.

### PART NUMBERS

KL-505	10 QT CASE
KL-505 55 GL	55 GAL DRUM
KL-505 30 GL	30 GAL DRUM

### RECOMMENDED APPLICATIONS

Motorcycle/ATV:  
Forks and Shocks

Snowmobile:  
Shocks