



Flex Drive® 30 Transmission Lube

Klotz Flex Drive® 30 TechniPlate® Synthetic Gear Lubricant is a low viscosity, Extreme pressure 75W/80 gear lubricant for use in 2/4-stroke motorcycle and ATV Transmissions with a wet clutch. Klotz Flex Drive® 30 is engineered for enhanced thermal stability and the constant shearing stress of racing applications. TechniPlate® technology is an advanced synthetic lubricant system that contains precision lubricating and anti-shear film to absorb shock and metal to metal contact. Klotz Flex Drive® 30 will challenge and outrun the competition in the following ways:

- **TechniPlate® reduced friction for improved gear reliability**
- **Fast, easy shifting and positive, smooth clutch operation**
- **Shear stable polymer molecules reduce shock loading**
- **Extreme load carrying capacity for extended bearing and gear life**
- **Protects against wear and quiets transmission gear noise**
- **Reduces gear and clutch temperature**
- **Extends clutch life and reduces slippage for positive lockup**
- **Anti-Oxidation protection against rust and corrosion**



CHARACTERISTICS

Film Strength	10
Pour Point	-36°F
Flash Point	480°F
Maximum RPM	N/A
Viscosity @ 100°C	7.00 cSt Min 11.00 cSt Max 10.10 cSt Typical
Product Color	Red
Chemical	100% Pure Synthetic
Biodegradable	60%

CERTIFICATIONS

Meets and exceeds manufacturer warranty requirements for Honda®, Kawasaki®, Suzuki®, Polaris®, KTM® transmissions and clutches.

DIRECTIONS

Fill to manufacturer's recommended level. Replaces S.A.E. 30, 40 and 50W gear oils.

COMPATIBILITY

Will blend with petroleum and synthetic based oils.

PART NUMBERS

KL-506	10 QT CASE
KL-506 30 GL	30 GAL DRUM
KL-506 55 GL	55 GAL DRUM

RECOMMENDED APPLICATIONS

Motorcycle/ATV:

2/4-Stroke Transmissions

Shifter Kart/Micro Sprints:

2/4-Stroke Transmissions

Marine Drag Boat:

Outboard Lower Units