SYNTHETIC LUBRICANT



Motorcycle TechniPlate® 10W/30

Klotz Motorcycle TechniPlate® hi-performance lubricant is backed by decades of racing experience. Designed for use in all 4-stroke hi-performance motorcycle engines with or without a wet clutch or integrated transmission.

Klotz Motorcycle TechniPlate® will challenge and outrun the competition in the following ways:

- Provides smoother, quieter clutch and transmission operation
- Thermally stable in Hi-RPM applications for increased horsepower
- TechniPlate® lubricity system for superior film strength and anti-scuff protection
- High load carrying capacity for reduced bearing and ring wear
- Superior thermal transfer for reduced engine temperatures
- Extends camshaft, lifter and bucket life
- Shear resistant anti-foam polymers maintain optimum lubrication
- Superior sealing for more power
- Anti-Oxidation protection against rust and corrosion

CHARACTERISTICS

Film Strength 10 Scale 1 = Failure - 10 = No Wear Pour Point -29°F Flash Point 480°F Maximum RPM Unlimited Viscosity @ 100°C 9.30 cSt Min 12.50 cSt Max 10.30 cSt Typical Product Color Red Chemical 100% Pure Synthetic Biodegradable 60%

CERTIFICATIONS

API SN JASO MA2 (T903:2016)

DIRECTIONS

Fill crankcase to manufacturer's recommended level

COMPATIBILITY

Methanol Alcohol NOS systems E-85 Gasoline

Blends with petroleum and most synthetic oils

PART NUMBERS

KL-830	10 QT CASE
KL-830 30 GL	30 GAL DRUM
KL-830 55 GL	55 GAL DRUM

RECOMMENDED APPLICATIONS

<u>4-Stroke Motorcycle</u> Stock/ Modified Street Hi-Performance Drag Racing Road Racing

Legends Dwarf Cars Oval Racing Road Racing

