



SYNTHETIC ENGINE LUBRICANT

Motorcycle TechniPlate® 20W/50

Klotz Motorcycle TechniPlate® hi-performance lubricant is backed by decades of racing experience. Designed for use in all 4-stroke hi-performance motorcycle engines with or without a wet clutch or integrated transmission.

Klotz Motorcycle TechniPlate will challenge and outrun the competition in the following ways:

- Provides smoother, quieter clutch and transmission operation
- Thermally stable in Hi-RPM applications for increased horsepower
- TechniPlate® lubricity system for superior film strength and anti-scuff protection OR TechniPlate® Peak Film Strength and Anti-Wear protection
- High Load Carrying Capacity for reduced bearing and ring wear
- Superior thermal transfer for reduced engine temperatures
- Extends camshaft, lifter and bucket life
- Shear resistant anti-foam polymers maintain optimum lubrication
- Superior sealing for more power
- Anti-Oxidation protection against rust and corrosion



CHARACTERISTICS

Film Strength	10	Scale 1 = Failure - 10 = No Wear
Pour Point	-29°F	
Flash Point	480°F	
Maximum RPM	Unlimited	
Viscosity @ 100°C	16.30 cSt Min 21.90 cSt Max	18.20 cSt Typical
Product Color	Red	
Chemical	100% Pure Synthetic	
Biodegradable	60%	

CERTIFICATIONS

API SJ/SN
JASO MA2

DIRECTIONS

Fill crankcase to manufacturer's recommended level

COMPATIBILITY

Methanol Alcohol	E-85
NOS systems	Gasoline

Blends with petroleum and most synthetic oils

PART NUMBERS

KL-850	10 QT CASE
KL-850 30 GL	30 GAL DRUM

RECOMMENDED APPLICATIONS

4-Stroke Motorcycle
Stock/ Modified Street
Hi-Performance
Drag Racing
Road Racing

Legends Dwarf Cars
Oval Racing
Road Racing