



# INSTALLATION INSTRUCTIONS

Part Number HA-2500-1

Congratulations, you have purchased the finest [air filter](#) that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N Filtercharger® seals properly.

## INSTALLATION

1. Remove the stock air filter.
2. Carefully clean the inside of the air box.
3. Remove the stock o-ring from the air box base. (Fig. 1)
4. Apply a light coating of the provided K&N Sealing Grease into the air box base o-ring groove.  
**Note:** This groove is for the o-ring removed in step 3.
5. Install the K&N Filtercharger® making sure it is completely seated.
6. Reinstall the two air filter screws on the K&N Filtercharger®. (Fig. 2)  
**Note:** Do not overtighten or damage to the K&N Filtercharger® can occur.
7. Reinstall the air box lid and tighten screws.

**THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.**




Fig. 1




Fig. 2