



# INSTALLATION INSTRUCTIONS

## Part Number: HD-1212

Congratulations, you have purchased the finest [air filter](#) that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N® air filter seals properly.

### INSTALLATION:

1. Remove the stock air filter.
2. Carefully pry the stock air cleaner cover bracket off of the stock air filter. (Fig. 1)
3. Install stock air cleaner cover bracket onto K&N® filter and install screws. (Fig. 2)
4. Install the provided gasket onto the stock screws on the back of the K&N® Filter. (Fig. 3)
5. Install the K&N® Filter onto the stock air cleaner base and make sure it is completely seated.
6. Tighten the stock screws a few threads at a time in a clockwise pattern to insure the K&N® Filter is installed evenly.
7. Reinstall the stock air cleaner cover and tighten the screws.

**THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.**



Fig. 1



Fig. 2



Fig. 3