



INSTALLATION INSTRUCTIONS

Part Number KA-9006

Congratulations, you have just purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N® air filter seals properly.

INSTALLATION:

1. Remove the four air cleaner cover screws and remove the cover.
2. Remove the air filter screw and remove the stock [air filter](#). (Fig 1)
3. Remove the 4 spacers from the stock air filter and install into the holes of the K&N® air filter. For removal from OE filter, use a screw driver to push spacers out. (Fig. 2)
4. Install the four OE spacers into the K&N® air filter. (Fig. 3)
5. Install the K&N® air filter into the air box and tighten the filter screw.

NOTE: K&N air filter will only fit one way into the air box.

6. Reinstall the air cleaner cover.
7. Reinstall the four air cleaner cover screws and tighten.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2



Fig. 3