



INSTALLATION INSTRUCTIONS

Part Number YA-4510

Congratulations, you have purchased the finest [air filter](#) that money can buy. With proper care, this filter can last many seasons. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N® air filter seals properly.

INSTALLATION:

- 1) Remove air box cover from air box and unclasp strap and remove OE cage.
NOTE: Plastic OE cage will be used with K&N® filter. (Fig. 1)
- 2) Remove OE foam filter(s), both the main filter and secondary filter and flame arrestor. These components are not needed with K&N® air filter. **(Fig. 2)**
- 3) Clean all sealing surfaces of air box.
- 4) Install K&N® air filter into air box. K&N® will only fit in one direction, K&N® logo at the top, narrow side of filter towards the top of air box. **(Fig. 3)**
- 5) Re-install plastic cage on top of K&N® and re-attach clasp. **(Fig. 4)**
- 6) Re-install air box cover onto air box.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2



Fig. 3



Fig. 4