



EXTENDED GIRDER BRAKE PEDAL 1071

FITS: '08-UP ELECTRA GLIDES, ROAD GLIDES, STREET GLIDES & ROAD KINGS

PARTS INCLUDED

- 1 Extended Girder Brake Pedal
- 1 Cotter Pin
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

WARNING! THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION! This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

TOOLS SUGGESTED

Set of Hex Wrenches, Needle Nose Pliers, Set of Socket Wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

PROCEDURE

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface; turn off the ignition and allow the engine to cool.

WARNING! YOU WILL BE WORKING AROUND THE ENGINE AND EXHAUST SYSTEM DURING INSTALLATION. ENSURE THAT THE ENGINE AND EXHAUST SYSTEM HAVE FULLY COOLED TO PREVENT INJURY.

STEP 2 Remove the footboard to gain access to the brake pedal.

STEP 3 Remove the small cotter pin, flat washer and linkage pin from the stock brake-linkage arm. Keep the washer and linkage pin that were removed, they will be re-used.

STEP 4 Remove the stock brake pedal, keep all hardware. Clean and apply grease to the pivot shaft.

STEP 5 Install the new brake pedal on to the pivot shaft and replace the hardware removed in Step 4.

STEP 6 Re-attach the linkage arm hardware that was removed in Step 3. A new cotter pin is provided in the kit.

STEP 7 Reinstall the footboard removed in Step 2.

STEP 8 Test for proper brake function and inspect for any possible interferences. Grease the arm regularly to ensure proper function.

CAUTION! ENSURE THAT THE INSTALLATION OF THIS PRODUCT DOES NOT INTERFERE WITH THE PROPER OPERATION OF THE MOTORCYCLE BEFORE RIDING.

ATTENTION! It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.

Ride On!

Küryakyn®

PAGE
2

EXTENDED GIRDER BRAKE PEDAL INSTALLATION