

Speedometer Trim Ring w/Visor

112

PARTS INCLUDED

- 1 speedometer trim ring
- 2 silicone tubes- <u>may not require use of both</u>
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

WARNING! THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING

THE CONTENTS DESCRIBED HEREIN CAN RESULT IN

POTENTIAL DEATH OR SERIOUS INJURY

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein

may negatively affect product performance and functionality.

TOOLS SUGGESTED

Blue masking tape

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

STEP 2 Clean existing trim ring on speedometer with an ammonia based cleaner. (Windex)

STEP 3 Center trim ring on speedometer. Mark dash and trim with a small piece of tape or

non-permanent marker.

ATTENTION! Ensure the area of installation is free of grease, oil, dirt or other debris to ensure

proper adhesion. Küryakyn WILL NOT issue a warranty on any parts lost due to

improper installation.

ATTENTION! The adhesive will not bond correctly if applied at temperatures less than 50°F. Do

not attempt this installation in temperatures less than 50°F.

STEP 4 Using the provided silicone, place a bead evenly around the inside of the new trim

ring.

STEP 5 Using centering mark, install trim ring to top of speedometer. Press firmly.

STEP 6 Using masking tape, secure the trim ring in four places. Let dry for one hour before

riding. Permanent bonding takes 24 hours.

Ride On!