

INSTALLATION INSTRUCTIONS

REPLACEMENT BASKET FOR DRINK HOLDER

1429

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- 1 Replacement Basket

YOU WILL ALSO NEED:

Scissors

FITS: UNIVERSAL DRINK HOLDER WITH BASKET, KURYAKYN P/N 1422

NOTICE THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

- STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.
- STEP 2** Unscrew the thumbnut & remove the drink holder from the handlebar clamp.
- STEP 3** Refer to PIC 1. Pull out on the rubber darts and cut them off with a pair of scissors behind the head of the rubber dart.
- STEP 4** Refer to PIC 2. Hold the replacement basket up to the support ring so that the notch in the basket will be centered in the two halves of the support ring as shown in PIC 2.
- STEP 5** Start at one end of the support ring, insert the dart into the hole and gently pull it through while pushing from the backside of the basket until the head of the dart is through the hole.
- STEP 6** Repeat the process for all of the darts.

Note: It may be helpful to pull on the upper portion of the replacement basket as shown in PIC 3 to help align the darts with the holes.

- STEP 7** Reinstall the drink holder to the handlebar clamp and secure with the thumbnut that was removed in STEP 2.

NOTICE IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.



PIC 1



PIC 2



PIC 3