



**PASSENGER DRINK HOLDER WITH BASKET**

**1 4 8 4**

**FITS-1/2" PASSENGER GRAB RAILS ON ELECTRA/TOUR GLIDES OR UNIVERSAL FIT ON 1/2", 5/8", OR 3/4" TUBES**

**PARTS INCLUDED**

- 1 3/4" bar clamp
- 1 Reducing Ring Kit
- 1 Universal Drink Holder Assembly
- 1 Anti Seize Packet
- 1 Hardware Kit
  - 1 Thumb Nut
  - 1 Split Lock Washer
  - 2 Shim Washers
- 1 Installation Instructions

*Please read and understand entire instructions before starting installation.*

**THANK YOU FOR CHOOSING KÜRYAKYN!**

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.**

**WARNING!** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

**CAUTION!** This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

**ATTENTION!** This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

**TOOLS SUGGESTED**

Set of hex wrenches

**STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.**

**PROCEDURE** - *Please note that all hardware included may not be used for installation*

**STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface; turn off the ignition and allow the engine to cool.

**STEP 2** Determine a suitable mounting location for the Drink Holder. Ensure that the mounting location will not interfere with the normal operation of the motorcycle.

**WARNING!** IMPROPER INSTALLATION OR USE OF THIS PRODUCT COULD RESULT IN SERIOUS INJURY OR DEATH.

**CAUTION!** Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

**-cont.-**

**CAUTION!** Avoid damage to the motorcycle. Protect painted surfaces with a soft cloth or blanket.

**ATTENTION!** Determine the mounting location and orientation of the Drink Holder before fully tightening the two screws. The clamp may leave marks on the rail when tightened down.

**NOTE** The clamp may be fit with the pivot hole above or below the bar depending on clearance.

**STEP 3** Remove the two screws from the clamp.

**STEP 4** Hold the clamp halves together on the rail in the desired location. Determine which (if any) aluminum spacers are needed to ensure proper fitment to the intended rail. Add anti seize to the threads and re-install the two screws from Step 3; leave the screws finger tight for now.

**STEP 5** Insert the Drink Holder pivot shaft into the pivot hole in the clamp.

**STEP 6** As shown in PIC 1, place the split lock washer on the stud. Apply a small amount of anti seize to the threads and secure the Drink Holder to the clamp with the thumb nut.

**STEP 7** Once you have the Drink Holder in the desired position, ensure that it will not interfere with the proper operation of the motorcycle.

**STEP 8** Tighten the two screws in the clamp and the thumb nut.

**CAUTION!** The adjustability of the Drink Holder was not intended to prevent spills.

**ATTENTION!** It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not warranty components lost due to improper installation. Periodic maintenance may be required.

**WARNING! TO PREVENT POSSIBLE LOSS OF CONTROL, WHICH COULD RESULT IN A POSSIBLE INJURY OR DEATH, WE DO NOT RECOMMEND REMOVING AND REPLACING CUP WHILE RIDING THE MOTORCYCLE.**

**CAUTION!** Do not overload the Drink Holder with excessive weight.

*Ride On!*

**Kuryakyn**<sup>®</sup>

PIC. 1



**PAGE**

**2**