



TECH-CONNECT DEVICE HOLDER for PERCH MOUNT 1698

PARTS INCLUDED

- 1 Tech-Connect Device Holder with Pivot Mount—Black
- 1 Thin Foam Pad with Adhesive Back
- 1 Perch Mount—Black
- 1 Hardware Kit Containing:
 - 2 Perch Mount Spacers
 - 2 1/4"-20 X 2" Button Socket Cap Screws
 - 2 1/4"-20 X 2-1/4" Button Socket Cap Screws
 - 2 M6 X 1.0 X 55mm Button Socket Cap Screws
 - 3 1/4" Flat Washers
 - 1 1/4" Lock Washer
 - 1 1/4" Low Crown Acorn Nut
 - 4 6" Black Nylon Cable Ties
 - 1 Package Anti Seize
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND NOTICES REGARDING THE USE AND CARE OF THIS PRODUCT.

WARNING	THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.
NOTICE	This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.
CAUTION	This indication alerts you to the fact that ignoring the contents described herein can result in potential injury.

NOTICE

IF INSTALLING THIS PRODUCT FOR ANOTHER PARTY, PLEASE MAKE SURE THEY RECEIVE THIS COPY OF THE INSTALLATION INSTRUCTIONS SO THEY ARE AWARE OF THE IMPORTANT INFORMATION CONTAINED IN THEM.

TOOLS SUGGESTED

Set Of Hex Wrenches, Set of Combination Wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

NOTE: For devices measuring 1-5/8" to 3-5/8" wide.

NOTICE

Avoid damage to the motorcycle. Protect painted surfaces with a soft cloth or blanket.

STEP 2 Place a clean, soft blanket over the gas tank to protect the paint.

CAUTION Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

NOTICE It is the installer's responsibility to ensure that there is adequate clearance between the Tech-Connect and any painted surfaces. Küryakyn is not responsible for any damage due to inadequate clearance.

NOTICE Be aware of any cables/wires that could potentially be pinched or crushed while using this product.

STEP 3 Remove the bottom screw securing the clutch perch halves. Set this aside, it will not be used again.

STEP 4 Identify the correct screw, either the metric or standard, by comparing threads on the included screws to the threads from the screws that were removed. The 1/4"-20 x 2-1/4" screws are generally used on older H-D motorcycles, the 1/4"-20 X 2" screws on newer Harleys and the M6 X 1.0 X 55mm on Metric bikes.

NOTICE Use the supplied anti-seize for fasteners; this will prevent galling and make future removal of fasteners easier.

STEP 5 As shown in PIC 2, insert the two included spacers into the two slots in the perch mount. Place a washer over one of the button socket cap screws, then insert it through the bottom spacer on the perch mount arm. Add a dab of anti-seize to the screw end.

STEP 6 As shown in PIC 3, place the arm, screw, washer and spacer on the perch and start the screw. Finger tighten the screw.

STEP 7 Remove the upper screw securing the perch mounting halves; it will not be used again. PIC 3

STEP 8 Rotate the arm up into position and install the screw, and washer while using a dab of anti-seize on the screw end. PIC 4





STEP 9 Tighten both of the screws securely.

STEP 10 Install the Tech-Connect holder to the handlebar mount by inserting the metal shaft through the hole in the handlebar mount. The hex flats on the metal shaft will line up with the hex flats in the hole. PIC 5 Secure the Tech-Connect with the included 1/4" flat washer, then the 1/4" lock washer, then the Acorn nut. PIC 6 Tighten securely.

STEP 11 Turn the handlebars in both directions to their full stop position and ensure that there is clearance between the mounting plate/Accessory and the gas tank, dash and other accessories.

WARNING ENSURE THAT THERE IS CLEARANCE AT ALL POINTS WHEN THE HANDLEBARS ARE TURNED, INSUFFICIENT CLEARANCE MAY CAUSE DAMAGE TO THE MOTORCYCLE OR CAN CAUSE LOSS OF CONTROL THAT COULD RESULT IN SEVERE INJURY OR DEATH.

NOTICE It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.



⚠ WARNING TO PREVENT POSSIBLE LOSS OF CONTROL, WHICH COULD RESULT IN SERIOUS INJURY OR DEATH, WE DO NOT RECOMMEND REMOVING, REPLACING OR OPERATING THE DEVICE IN THE TECH-CONNECT WHILE RIDING THE MOTORCYCLE .

USING THE TECH-CONNECT HOLDER

STEP 1 Open the Tech-Connect Holder so the sides are separated from the center section. Peel the narrow pieces of foam off the backing paper, center them in the inset portion of the sides and apply them to the sides of the holder. Peel the wide piece of foam from the backing paper, center it in the inset portion in the center and apply it to the center of the holder. PIC 7

STEP 2 To adjust the opening in the Tech-Connect larger, turn the knobs on the outside of the Tech-Connect (PIC 7) counter clockwise until your device will fit in between the arms. Turn the knobs clockwise to close the arms around the device. There is a locking detent under the knobs to hold them in place once they come in contact with the device. **DO NOT over tighten the knobs. Tightening them too tight will not allow you to loosen them with your fingers.** Periodically check the tightness of the mobile device in the Tech-Connect.

NOTE: For best results keep "L" shaped foot portion of the Tech-Connect Holder on the bottom of the device. Keep the device holding support arms centered on the mounting plate.

STEP 3 To remove the Tech-Connect from the bike for storage, loosen the tensioning nut on the back side of the holder until it clears the threads. PIC 6 Snap the Tech-Connect holder off of the ball. PIC 8 Remove the tension nut and thread it to the Tech-Connect holder for storage.




STEP 4 To replace the Tech-Connect on the swivel ball, remove the tension nut from the back. Slide the tension nut over the swivel ball, snap the Tech-Connect back on the swivel ball and thread the tension nut onto the Tech-Connect. Tighten the tension nut to the desired tension.

STEP 5 To adjust the angle of the Tech-Connect, loosen the tensioning nut, adjust the Tech-Connect to the desired position and tighten the tension nut. PIC 6 The tension nut will allow you to keep the Tech-Connect in the same position or, with a little less tightness, allow you to move the Tech-Connect on the swivel ball.

⚠ WARNING DO NOT ATTEMPT TO OPERATE OR REMOVE THE MOBILE DEVICE FROM THE HOLDER WHILE OPERATING THE MOTORCYCLE.

NOTICE Ensure that the Mobile Device is secure in the Tech-Connect Holder. Küryakyn is not responsible for any Device that is stolen or damaged from use in this Holder or from the Holder not being properly secured to the motorcycle. It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.

NOTICE Motorcycling can be done in a harsh environment. Make sure your Mobile Device is appropriate for this application.



Ride On!