



HEADLIGHT VISOR

2182

**FITS: UNIVERSAL FOR 7" HEADLIGHTS WITH RETAINER RING
H-D MODELS WITH 7" HEADLIGHTS
YAMAHA: ALL '99-UP ROAD STAR MODELS (EXCEPT WARRIOR), ALL '98-UP V STAR 1100 MODELS**

PARTS INCLUDED

- 1 Headlight Visor
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

TOOLS SUGGESTED

Set of hex wrenches, combination wrenches, and a screwdriver set.

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

PROCEDURE

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

STEP 2 Remove the stock headlight hardware. Unplug the headlight harness plug. Remove light from bike.

STEP 3 Set light on a soft towel or equivalent to prevent any scratches.

STEP 4 Remove the hardware that secures headlight bezel exposing the inner ring. [PIC. 1.](#)

STEP 5 With the headlight bezel removed from the light, remove the hardware that secures the inner ring to the headlight assembly.

STEP 6 Remove the inner ring from the light. Make note which way the tabs line up.

STEP 7 With the inner ring in hand fit the new headlight visor on the top inside of the ring.

STEP 8 Once satisfied with the fitment you can reapply the inner ring with the new headlight visor to the light housing and secure it with stock hardware removed in step 5.

STEP 9 With all the inner hardware fastened to the headlight, plug-in and mount the headlight back in the housing using the stock hardware.

PIC. 1



PIC. 2



Ride On!