



PILOT SHIFT PEG

4426

FITS ALL H-D SHIFT LEVERS WITH 5/16"-24 THREADED HOLE OR 5/16" THROUGH HOLE

PART #	INCLUDED
304426	1 Pilot Shift Peg
	1 5/16-24 x 1" HHCS Fastener
	1 1/4 Splined Lock Washer
	1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

PLEASE NOTE

It is the installers' responsibility to make sure all fasteners (including pre-assembled) are tightened before operation of motorcycle. Kuryakyn will not warranty components that are lost due to improper installation. Periodic maintenance may be required.

TOOLS SUGGESTED

Tools necessary depend on the existing shift peg; stock shift pegs require Vise-Grip pliers for removal.

ATTENTION! A factory service manual may be helpful in performing this installation. Do not attempt to perform this installation if you are not confident in your ability to complete all steps in the procedure; consult a trained technician.

CAUTION! PREVENT POTENTIAL SERIOUS INJURIES; BE SURE ALL FASTENERS ARE SECURE BEFORE RIDING.

PROCEDURE

STEP 1 Use Vise-Grip pliers to remove a stock shift peg (see [PIC.1](#)). For Screamin' Eagle or CVO models, refer to your factory service manual for specific instructions on removing the shift peg.

STEP 2 Install the pilot shift peg onto the shift lever; secure with the supplied fastener and splined lock washer (see [PIC.2](#)).

*Ride
On!*

