

INSTALLATION INSTRUCTIONS

XKURSION XT CO-PILOT TANK BAG

5294

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

MARNING

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

A CAUTION

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

1 Tank Bag 1 Strap - Bag Harness

Sun Screen 1 Strap - Fork Strap
Rain Cover 1 Strap - Frame Strap

1 Sunglasses Holder 2 Strap - Single Male Buckle with Loop

NOTICE

1

1

THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1

Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

▲ CAUTION

KURYAKYN IS NOT RESPONSIBLE FOR IMPROPER LOADS OR UNSAFE POSITIONING OF THE XKURSION XT CO-PILOT TANK BAG. BE SURE THE WEIGHT OF THE CONTENTS IN THE BAG DOES NOT EXCEED SAFE LIMITS. IT IS THE RIDERS RESPONSIBILITY TO DETERMINE WHAT THE SAFE LIMIT IS BASED ON THE POSITION OF THE BAG, PROPER SECURING OF THE BAG AND WEIGHT LIMITS CALLED OUT BY THE MANUFACTURER OF THE MOTORCYCLE.

NOTICE

ATTACHING THIS BAG TO YOUR MOTORCYCLE MAY MAR, DULL, OR SCRATCH THE SURFACE TO WHICH IT IS ATTACHED.

KURYAKYN WILL NOT REPLACE ANY PARTS DAMAGED BY INSTALLATION OF THIS BAG. KEEP THE MAGNETIC MOUNTING PAD SURFACE AS CLEAN AS POSSIBLE TO REDUCE DAMAGE. THOROUGHLY CLEAN THE MOUNTING SURFACE BEFORE ATTACHING THE MOUNTING PAD.

IT IS THE END USER'S RESPONSIBILITY TO UNDERSTAND THAT PLACING ITEMS ON PAINTED SURFACES MAY CAUSE DAMAGE.

THE XKURSION XT CO-PILOT TANK BAG IS INTENDED FOR MOUNTING ON FUEL TANK (WITH OR WITHOUT CENTER DASH PANEL). MOUNT TO MAGNETIC TANKS USING THE INCLUDED MAGNETIC MOUNTING PAD OR USE FORK STRAP AND FRAME STRAP TO MOUNT ON NON-MAGNETIC TANKS.

WARNING

DO NOT ATTEMPT TO USE YOUR DEVICE WHILE OPERATING THE MOTORCYCLE. KEEP YOUR EYES ON THE ROAD. DISTRACTED RIDING CAN CAUSE A CRASH RESULTING IN DEATH OR SERIOUS INJURY.





INSTALLATION INSTRUCTIONS

XKURSION XT CO-PILOT TANK BAG

5294

-CONTINUED-

▲ WARNING

PREVENT POTENTIAL SERIOUS INJURY! ENSURE BAG IS FASTENED AND STRAPS ARE SECURE BEFORE RIDING THE MOTORCYCLE.

NOTICE

THIS BAG IS NOT WATER-PROOF. USE THE INCLUDED RAIN COVER IN INCLEMENT WEATHER TO ASSIST IN PROVIDING A WEATHER-RESISTANT STORAGE AREA.

▲ WARNING

DO NOT ATTEMPT TO ACCESS STORED ITEMS WHILE DRIVING. DO NOT DISTRACT YOURSELF. DISTRACTED RIDING CAN CAUSE A CRASH RESULTING IN DEATH OR SERIOUS INJURY.

FEATURES

- Magnetic tank mounting base with optional mounting strap kit
- High contrast visibility liner
- Grey reflective elements on the outside of the bag
- Touch-sensitive clear window
- Touch-sensitive rain cover, and its own stowaway pocket
- Detachable sun screen cover
- Glove friendly zipper pulls
- Magnetic harness
- Electronics storage for up to a 12" tablet
- Audio/power ports
- Formed and removable sunglasses case that mounts in place
- Key clip and catch-all pockets
- Low profile handle

MOUNTING

Typical Installation: The Xkursion XT Co-Pilot Tank Bag (with Removable SUGGESTIONS Magnetic Mounting Pad) is intended to install on most fuel tanks (with or without a center dash).

> Remove the bag from the Removable Magnetic Mount Pad at the hook and loop point on the bottom side of the bag.

Using Straps:

- FRAME STRAP: connects to bottom female buckles of bag harness strap. Connect strap buckle to harness buckle on one side, wrap the strap down/around/under the tank and frame, and connect it to the other bottom female buckle. Tighten straps as needed.
- FORK STRAP: connects to top female buckles of bag harness strap. Connect strap buckle to harness buckle on one side, wrap the strap around the motorcycle's neck, and connect it to the other top female buckle. Tighten straps as needed.
- SINGLE MALE BUCKLE WITH LOOP: connects to top or bottom female buckles of bag harness strap. Determine mounting point (neck, fork covers, etc). Wrap strap around mounting point, feed the buckle end of the strap through the loop, and cinch loop tight. Connect strap to harness buckle. Tighten straps as needed.

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.



