

INSTALLATION INSTRUCTIONS

DASH CONSOLE BY JIM NASI, GLOSS BLACK

5689

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- 1 Dash Console

YOU WILL ALSO NEED:

Hex wrench set, Phillips screw driver

PICTURES SHOWN ARE OF THE CHROME PARTS. INSTALLATION OF THE BLACK PARTS WILL BE THE SAME.

NOTICE THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

STEP 2 Remove the seat and hardware. Set all aside; they will be reused later.

Remove existing dash console and hardware. Set the hardware aside; it will be reused later.

Remove the gaskets, mounting bracket, and hardware from dash console. Set all aside; they will be reused.

Note: Refer to your motorcycle's service manual for assistance in removal of the seat and dash console.

STEP 3 Refer to PIC 1. Locate Nasi Dash Console. Locate the gaskets that were removed in Step 2 and place it on the bottom side edges of the console. The gaskets should be positioned a 1/2" from the rear end of the console.

STEP 4 Refer to PIC 2. Locate the mounting bracket and hardware that was removed in Step 2 and fasten it to the console.



INSTALLATION INSTRUCTIONS

DASH CONSOLE BY JIM NASI, GLOSS BLACK

5689

-CONTINUED-

- STEP 5** Refer to PIC 3. Align and place the dash on the fuel tank. Fasten the console down to the fuel tank using hardware that was removed in Step 2.

Note: Be careful that the gaskets do not move out of place before fastening it down.

- STEP 6** Place existing or new gas cap into dash console.

- STEP 7** Reattach the seat.



PIC 3



FINAL

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.