

INSTALLATION INSTRUCTIONS

SPEAR SHIFT & BRAKE PEG, CHROME

5750

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

MARNING

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

A CAUTION

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- Shift or Brake Peg
- 1 M8 X 1.25 X 90mm Socket Head Cap Screw
- 1 Internal Tooth Lock Washer

YOU WILL ALSO NEED:

Pliers, metric hex wrench set

NOTICE

THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1

Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

M8 X 1.25 X 90MM SHCS SHIFT OR BRAKE

STEP 2

Refer to PIC 2. Remove existing shift or brake peg from lever. Set peg and hardware aside, they will not be reused.

SHIFT LEVER (LEFT) SIDE SHOWN

STEP 3

Refer to PIC 3. Locate provided peg, screw, and internal tooth washer. Insert the screw through the front of the peg. Place the washer onto the protruding screw on the back end of the peg.

PIC 3

PIC 1

LOCK WASHER

Refer to PIC 4. Align and fasten the peg assembly to the shift or brake lever. Adjust the peg to desired position and fully tighten hardware.





INSTALLATION INSTRUCTIONS

SPEAR SHIFT & BRAKE PEG, CHROME

5750

-CONTINUED-

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.